


1 LOCATION OF WATER WELL: County: Chase Fraction: NW 1/4 NW 1/4 SE 1/4 Section Number: 28 Township Number: T 20 S Range Number: R 8 E

Distance and direction from nearest town or city street address of well if located within city?
3/4 Mile North of BAZZAR

2 WATER WELL OWNER: Elppre Stoute RR#, St. Address, Box #: RT City, State, ZIP Code: Collanwood Falls, Ks 66845 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION: 20 ft. below land surface measured on mo/day/yr May 4 96

Depth(s) Groundwater Encountered 1. 20 ft. 2. 20 ft. 3. 45 ft.

WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr May 4 96

Pump test data: Well water was 5 gpm after 7 hours pumping 45 gpm

Est. Yield 5 gpm Well water was 9 ft. after 7 hours pumping 45 gpm

Bore Hole Diameter 9 in. to 28 ft. and 7 in. to 45 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 5 in. to 28 ft. Dia. 18 in. to 28 ft. Dia. 7 in. to 26 ft. Dia. SDR-26

Casing height above land surface 5 in. weight 18 lbs./ft. Wall thickness or gauge No. SDR-26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 28 ft. to 45 ft. From 28 ft. to 45 ft. From 28 ft. to 45 ft. From 28 ft. to 45 ft.

GRAVEL PACK INTERVALS: From 23 ft. to 45 ft. From 23 ft. to 45 ft. From 23 ft. to 45 ft. From 23 ft. to 45 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 23 ft. to 23 ft. From 23 ft. to 23 ft. From 23 ft. to 23 ft. From 23 ft. to 23 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Rail Road
 13 Insecticide storage

Direction from well? East How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top Soil			
4	10	Clay TAN			
10	17	Shale Red			
17	28	Red Sticky Clay Mixed with some Gravel			
28	33	LIME Fractured Gray			
33	35	LIME - Solid - Light Gray			
35	39	Shale Green			
39	45	LIME Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 15 96 May 4 96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 210 This Water Well Record was completed on (mo/day/yr) MAY 15 96 under the business name of Zinn Water Well Dring by (signature) Joseph A. Zinn

OFFICE USE ONLY
T
R
EW
SEC.