| 219 WATER | 8587 R WELL | Well #3 RECORD | Form WWC- | 5 | Division of Wate | er Resources; App. No. | 46,498 | |
|---|---|--|-------------------------------|--|---|------------------------|---------|--|
| 1 LOCATION OF WATER WELL: | | | Fraction | | Section Number | | | |
| | ty: Rice | | SE 1/4 NE 1/4 N | | 27 | T 20 S | R 8 E W | |
| Distan within | city? Apr | ction from nearest town or city proximately 3 1/2 miles so | street address of well if loo | eated | Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 38.286982 | | | |
| walling only a process of the same of the | | | | | Longitude: -98.192684 | | | |
| 2 WATER WELL OWNER: JACAM Chemicals LLC | | | | | Elevation: Unknown | | | |
| RR#, St. Address, Box # 205 South Broadway | | | | | Datum: NAD83 | | | |
| City, State, ZIP Code P.O. Box 96 Sterling, KS 67579 | | | | | Data Collection Method: WAAS GPS Unit | | | |
| 3 LOCA | TE WEI | | | 5 | 6 ft. | | 7777 | |
| LOCATION | | | | | | | | |
| WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft, WELL'S STATIC WATER LEVEL 12.0 ft. below land surface measured on mo/day/yr 03-19-08 | | | | | | | | |
| SECTION BOX: N Pump test data: Well water was Not checked ft. after hours pumping gpm | | | | | | | | |
| Est. Yield Unknown gpm: Well water wasft. after hours pumping gpm | | | | | | | | |
| WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well E 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) | | | | | | | | |
| | | | | | | | - | |
| 2 Irrigation (4) Industrial 7 Domestic (lawn & garden) 10 Monitoring well | | | | | | | | |
| sw | -SW SW Was a chemical/bacteriological sample submitted to Department? Yes No . If yes, mo/day/yrs | | | | | | | |
| | | | | | | | | |
| Sample was submitted Water well disinfected? Yes V No | | | | | | | | |
| 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued \(\) Clamped | | | | | | | | |
| 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded | | | | | | | | |
| 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 10 in. to 33 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in., weight 9.03 lbs./ft. Wall thickness or gauge No413 | | | | | | | | |
| Blank casing diameter 10 in. to 33 ft., Diameter in. to ft., Diameter in. to ft. | | | | | | | | |
| TVDE | E SCREET | U OD DEDEOD ATION MA | rediai. | 03 | ibs./it. wan thic | kness or gauge No. | .413 | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) | | | | | | | | |
| 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) | | | | | | | | |
| SCREEN OR PERFORATION OPENINGS ARE: | | | | | | | | |
| 1) Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) | | | | | | | | |
| 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify) | | | | | | | | |
| SCREEN-PERFORATED INTERVALS: From 33 ft. to 55 ft., From ft. to ft. | | | | | | | | |
| | From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 56 ft., From ft. to ft. | | | | | | | |
| GRAVEL PACK INTERVALS: From 25 ft. to 56 ft., From ft. to ft. From ft. to ft., From ft. to ft. | | | | | | | | |
| 6 GROUT MATERIAL: 1 Neat Cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug | | | | | | | | |
| Compacted Soil 5 | | | | | | | | |
| Compacted Soil Grout Intervals: From 0 ft. to 5 ft., From ft. to ft., From 5 ft. to 25 ft. What is the nearest source of possible contamination: | | | | | | | | |
| 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify | | | | | | | | |
| 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below) None known | | | | | | | | |
| 3 Watertight sewer lines 6 Scepage pit 9 Feedyard 12 Fertilizer Storage 13 On Wolf gas well | | | | | | | | |
| FROM | TO TO | l?LITHOLOGIC | | FROM | | PLUGGING INT | EDVAIC | |
| 0 | 3 | Topsoil | 200 | TROM | 10 | 1 LOGGING INTI | ERVALS | |
| 3 | 15 | Clay, brown | | | | | | |
| 15 | 36 | Sand and gravel, fine, n | nedium, coarse | | | | | |
| 36 | 46 | Clay, brown, some grav | el | | | | | |
| 46 | 55 | Sand and gravel, fine, n | nedium | | | | | |
| 55 | 56 | Clay, brown | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged | | | | | | | | |
| under my jurisdiction and was completed on (mo/day/year) U3-19-08 and this record is true to the best of my knowledge and belief. | | | | | | | | |
| Kansas Water Well Contractor's License No. 771 This Water Well Record was completed on (mo/day/year) 03-25-08 | | | | | | | | |
| | | ame of Clarke Well & Equ | | | (signature) | alex. | | |
| INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone | | | | | | | | |
| 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. | | | | | | | | |