WATER WELL RECORD	Form W	WC-5	Di	vision of Wate	r Resources App. N	0.	
1 LOCATION OF WATER WELL	: Fraction			on Number	Township No.	Range Number	
County: Marion	1/4 Se 1/4 Ne	1/4 Ne1/4			T 2/S	R / ZE-W	
Street/Rural Address of Well Locati					System (GPS) in		
from nearest town or intersection: If at owner's address, check here			Latitude:				
			Elevation:				
2 WATED WELL OWNED.	. Ora Niekal		Datum	<u>n</u> : 🔲 WGS 84	4, □ NAD 83, □	NAD 27	
2 WATER WELL OWNER: Dar Sie Nickel RR#, Street Address, Box #: 1177 Alama Rd				Collection Method: GPS unit (Make/Model:)			
City State 7IP Code			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
No	ewton, Ksb	7114	Est. A	ccuracy:	3 m, 3-5 m, 3	5-15 m, □ >15 m	
3 LOCATE WELL	OF COMPLETED WELI		3	ft.			
SECTION BOX: Depth(s) Gr	Depth(s) Groundwater Encountered (1)						
N WELL'S ST	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
р	Pump test data: Well water was						
W NW NE N							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
Denotes Denote the Constitution of the Constit							
Irrigatio	Irrigation Industrial Domestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
water wen distincted:							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Qued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Wall thickness or gauge No. 214.							
Casing height above land surface. 12 in. Weight SDR26.lbs./ft. Wall thickness or gauge No 2.14.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel PVC Other (Specify)							
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to 35 ft., From 5.5 ft. to 65 ft.							
SCREEN-PERFORATED INTERVALS: From 1.0. ft. to 2.3. ft., From 5.5. ft. to 65. ft. ft. ft. ft. ft. ft. ft. ft. ft. ft							
GRAVEL PACK INTERVA	LS: From 10	ft to	0	it., From ft From	ft.	to ft.	
GRAVED TACK INTERVAL	From	ft. to		ft., From	ft.	to ft.	
From							
Grout Intervals: From							
What is the nearest source of possible		□ Livesteels	nang	☐ Insecticide	storage	her (specify below)	
Septic tank					ner (specify octow)		
☐ Watertight sewer lines ☐ Seep	age pit 🔲 Feedyard	Fertilizer	storage	Oil well/g	as well		
Direction from well		T					
	LOGIC LOG	FROM	ТО	LITHO, L	OG (cont.) <u>or</u> PLU	UGGING INTERVALS	
0 3 Top Soil						1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
3 10 Clav		1					
	wter						
20 65 Blue 8,	hale						
					wp 4-4		
		-					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ∠ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year)							
Kansas Water Well Contractor's License No. 17 This Water Well Record was completed on (mo/day/year)							
under the business name of							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							