WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.				
1 LOCATION OF WATER		Fraction	. 1/ (0 1/		n Number	Township No.	Range Number	
County: Mario	L     I Location: if:	1/4 Se 1/4 Sw	direction	Global	<u>5</u> Positionina	T 3/ S System (GPS) in	R / ZE W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here Latitude:								
				Longitude: (in decimal degrees)				
					Elevation:			
2 WATER WELL OWNER: Gerold Unruh				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:				
RR#, Street Address, Box #: 374 Mach				GPS unit (Make/Model:)				
City, State, ZIP Code : Newton, Kob7/14			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m					
3 LOCATE WELL	IVEU	con, ny e	1117	ESI, AC	curacy.	л III, [] 3-3 III, []	J-1J III,     /1J III	
WITH AN "X" IN 4 D	EPTH OF C	OMPLETED WELI	7.0		ft.	'/ ·-	(2)	
SECTION BOX: Dep	Depth(s) Groundwater Encountered (1)							
N WELL'S STATIC WATER LEVEL								
EST. YIELD. S. Well water was					ft. after hours pumping gpm			
W Bore	erin. to	in. toft., andin. toft.						
WELL WATER TO BE USED AS: Public water				er supply				
SWSE Domestic Feedlot Oil field water supply Dewateri						matering [] Conitoring well		
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
S If yes, mo/day/yr sample was submitted								
1 mile  Water well disinfected?								
5 TYPE OF CASING USED: Steel Z-PVC Other								
CASING JOINTS: 4 Glued Clamped Welded Threaded								
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight DR261bs./ft., Wall thickness or gauge No. 2/4.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel TYC Other (Specify)								
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Government Torch out Drilled holes None (open hole)								
Continuous stot								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
what is the hearest source of possible contamination.  Septic tank  Lateral lines Pit privy  Livestock pens  Insecticide storage  Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Watertight sewer lines Seepage pit Feedyard Fertilizer sto								
Direction from well			rerunzer s  Distance	from we	ell	2. 41. hin . 50	261	
FROM TO	LITHOLOGI		FROM	ТО	LITHO. L	OG (cont.) <u>or</u> PLU	UGGING INTERVALS	
0 10 Clay								
10 20 Sand	+ Wat	rer						
	01.1	/°%						
20 15 15/08	Shall	bout of						
75 76 Crum	61005	shale + So	me Wa	ten				
76 90 6-nay	Shall				**************			
						AWAMP		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION; This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year)								
Kansas Water Well Contractor's License No								
under the business name of								
(white, blue, pink) to Kansas Depart	ment of Health a	nd Environment, Bureau	of Water, Geol	ogy Section	on, 1000 SW Ja	ackson St., Suite 420,	, Topeka, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at <a href="http://www.kdheks.gov/waterwell/index.html">http://www.kdheks.gov/waterwell/index.html</a> .								
KSA 82a-1212								