LOCATI	ON OF WA	TER WELL:	Fraction	VELL RECORD	Form vvv	Section Number		Number	Ranco	Number
1 LOCATION OF WATER WELL: County: Coffey			NE _{1/4}	NE 1/4	SE ¼	Section Number 27	T	21 S	R	15 EW
		from nearest town of					· ' · · · · · · · · · · · · · · · · · ·	44 0	1 7	12 GW
D10101100 0		4th and Lawr	•			··· ·				
O WATE	R WELL OW		disc, bull.	ingcom, non	<u> </u>					
_		x # Smitty's 1	Ango C/O Ja	mas MaCaa			Doord o	of America alta and I	Divinion of M	ator Descur
					•••			of Agriculture, [Division of W	ater Hesour
	, ZIP Code		awrence St.							
AN "X"	E WELL'S L IN SECTIO	OCATION WITH 4 De	DEPTH OF COM epth(s) Groundwat		<i>.</i>	ft. ELEVA				
_τ Γ	1		ELL'S STATIC WA		_					
	i i					ft. 8				
-	NW	NE						•		•
1	!		t. Yield							
. * w ├			re Hole Diameter							
<u> </u>	!		ELL WATER TO			water supply	8 Air condition	ū	Injection wel	
i l.	SW	SE	1 Domestic	3 Feedlot		d water supply		12	Other Speci	fy below)
	1		2 Irrigation	4 Industrial		and garden only				
↓ L	1	l Wa	as a chemical/bact	eriological sample	e submitted	to Department? Y	esNo	x; If yes,	, mo/day/yr s	ample was s
_		ş mit	tted			Wa	ater Well Disinfe	cted? Yes	No	X
5 TYPE	OF BLANK	CASING USED:	5	Wrought iron	8 C	oncrete tile	CASING	JOINTS: Glued	d <u> C</u> la	mped
1 St	eel	3 RMP (SR)	6	Asbestos-Cemen	t 9 O	ther (specify belo	w)	Weld	ed	
2 P\	/C	4 ABS	to 7	Fiberglass				Threa	aded	
Blank casi	ing diameter	9 in.	to / U	ft Dia	ir	n. to	ft Dia		in to X	
		∡ and surface		weight		PVCIbs.	ft. Wall thicknes	ss or gauge No	0	
•	•	R PERFORATION M		g	SCH 40	3VE	10 4	Asbestos-ceme	ent	
1 St		3 Stainless ste		Fiberglass	_	RMP (SR)		Other (specify)		
				-		ABS				
2 Br		4 Galvanized		Concrete tile	-			None used (op	•	
		RATION OPENINGS			zed wrappe	ea	8 Saw cut		11 None (d	pen hole)
	ontinuous slo				e wrapped		9 Drilled hole	es		
2 Lo	ouvered shut	ter 4 Key p	ounched //	7 Tore	ch sut		10 Other (spe	• /		
SCREEN-	PERFORAT	ED INTERVALS:	From !!	ft. to	20	ft., Fro	m	ft. to	o .	
	SMD		From			ft., Fro			o .	
4		CK INTERVALS:	From	ft. to			m	7.7.7 ft. to	o 	
			From 3	ft. to	20	ft., Fro	m	ft. te	0	
GROU	T MATERIAL	: _ 1 Neat cem	ent 2	ement grout						
Grout Inte	rvals: Fro	mO	<i>,</i> ,			ft. to			ft. to	
What is th	e nearest so	ource of possible con		·		-	stock pens		bandoned wa	ater-well
1 Se	eptic tank	4 Lateral li	nes	7 Pit privy		11 Fuel	•		il well/Gas w	
	ewer lines	5 Cess poo		8 Sewage la	moon		lizer storage	\sim 1	ther (specify	
		ver lines 6 Seepage		•	igoon		•	الوث	trier (specify	Delow)
	•	rei inles 6 Seepage	; pit	9 Feedyard			cticide storage			
Direction 1		r	LITHOLOGIC LOC	3	LEBO		iny feet?	PLUGGING II	minated	_Si
FROM	то		LITHOLOGIC LO		FRO	м то		, LOGGING II	VIERVALS	
				• • • • • • • • • • • • • • • • • • • •						
GL_	1.00	Soil								
1.00	11.00	Silty Clay	(CL)							
11.00	19.50	Clayey San				#* - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ### - ###				
19.50		Limestone	_ (50)							
20.00	TD	End of bor	ahal a							
20.00	10	ENG OF POL	CIOIC							
-							11 11 11 11 11 11			
										
							Flush Mount			
							Waiver			
	 						WOLVCL		-	
_							D. Taylor	•		
7 CONT	RACTOR'S	OR LANDOWNER'S	CERTIFICATION	This water well	was (17 cor	estructed Y2) reco	onstructed or	96 3) plugged und	ler mv jurisdi	ction and w
Completed	on (mo/day	/year) 129	-97	water well			ord is true to the			
				This Mater	Moll Boss				-97	Deliet. NamS
		's License No	585	inis water	AAGII LIGCOL	d was completed	1 1776	1	Do T	1
	business na	AFT				by (signa		1 VW	Tun L	uml
		pewriter or ball point pen. nent, Bureau of Water, Tope								Department