


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 21 Township Number T 21 S Range Number R 16 E W
 County: COFFEY

Distance and direction from nearest town or city street address of well if located within city?
1550 OXEN LANE NE ; BURLINGTON, KS LAT: 38.2133° (GOOGLE) LONG: -95.6563° (EARTH)

2 WATER WELL OWNER: WOLF CREEK NUCLEAR OPERATING PLANT
 RR#, St. Address, Box # : 1550 OXEN LANE, NE Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : BURLINGTON, KS 66839 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 4.3 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 1.9 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
MW-10C
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No (No)

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped
 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole) Threaded X
 Blank casing diameter 6 in. to 27 ft. Dia 2 in. to 33 ft. Dia in. to ft.
 Casing height above land surface 32 in., weight lbs./ft. Wall thickness or gauge No. SCH. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 RMP (SR) 8 ABS 9 Other (Specify) 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 33 ft. to 43 ft., From ft. to ft.
SAND PACK INTERVALS: From 3.1 ft. to 4.3 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 2 ft. to 31 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
COOLING LAKE
 Direction from well? WEST How many feet? 0.5 MILE

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4'	CLAY	+3'	2' BGS	5' x 4" x 4" ABOVE-GROUND STEEL WELL PROTECTOR
4'	16'	LIMESTONE			
16'	28'	SHALE			
28'	42'	LIMESTONE			
42'	43'	SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-20-09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 788 This Water Well Record was completed on (mo/day/yr) 8-18-09 under the business name of ROBERTS ENV. DRILLING, INC. by (signature) Charley Roberts

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367, Telephone 785-298-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.