WATER WELL RECORD Form WWC-5					Di	vision of Wate	er Resources App. N	[o. L	
1 LOCATION OF WATER WELL:			Fraction			on Number		Range Number	
County: COFFEY			1/4 NW 1/4 SW	/ ¼ NE ¼		7	T 21 S	R 16	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						Global Positioning System (GPS) information: Latitude:38.237327			
						Longitude:95.691695			
			CREEK NUCLEAR OP.CORP.			Collection Method:			
		MD C 1	(EN LANE NE						
			IGTON, KS 66839			☑ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☑ 5-15 m, ☐ >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 50 ft.									
	ELAN "A FION BO								
SEC.	N WELL'S STATIC WATER LEVEL. 2. 1t. (2)								
	Pump test data: Well water wasft. after hours pumping								
EST. YIELDgpm. Well water wasft. after									
W     E   Bore Hole Diameter									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well #MW-11B									
Was a chemical/bacteriological sample submitted to Department? Yes No									
S If yes, mo/day/yr sample was submitted									
Water well disinfected? ☐ Yes ☐ No									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 1									
Casing height above land surface. 27 in., Weight									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 59. ft. to 40. ft., From ft. to ft.									
From									
GRAVEL PACK INTERVALS: From									
From ft., to ft., From ft. to ft.									
6 GROUT MATERIAL: ☐ Neat cement  ☐ Cement grout  ☐ Bentonite- ☐ Other									
Grout Intervals: From 35 ft. to 2.5 ft., From 38 ft. to 35 ft., From ft. to ft.									
What is the nearest source of possible contamination:  ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)									
Sewer lines Cesspool Sewage lagoon Fuel storage Ahandoned water well									
Watertight sewer lines Seepage pit Feedvard Fertilizer storage Oil well/gas well COOLING LAKE									
		m well WEST & SOUTH					HAN 600 FT	ICCINIC INTERVALS	
FROM 0	TO 2'	LITHOLOG		FROM	TO	LITTO, LO	OG (cont.) or PLU	JGGING INTERVALS	
2'	6.5'	Brown Silty Clay w/ Gra	vei			-			
6.5'	13'	Sandy Clay Sandstone					- M		
13'	39.5'	Shale							
39.5'	50'	Limestone							
+2.5'	2.5'	4" X 5' AboveGround W	All Protector						
72.5	2.0	Completion w/2'x2'x2.5				-			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \( \bigsize \) constructed, \( \bigsize \) reconstructed, or \( \bigsize \) plugged									
under my jurisdiction and was completed on (mo/day/year)11/01/12 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No									
under the business name of									
		Use typewriter or ball point pen. o Kansas Department of Health							
		5522. Send one copy to WATI							
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212 (REDI JOB # 1822/72- AP) Check: White Copy, Blue Copy, Pink Copy									