


1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 NW 1/4 NE 1/4 Section Number 17 Township Number T 21 S Range Number R 22 EW  
 County Linn  
 Distance and direction from nearest town or city street address of well if located within city?  
Hwy 1077 Centerville, Ks.

2 WATER WELL OWNER: Keith & Tammy Brownback  
 RR#, St. Address, Box # P.O. Box 57  
 City, State, ZIP Code Centerville, Ks. 66014  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL: 10 ft. ELEVATION: 5/23/00  
 AN "X" IN SECTION BOX:  
  
 Depth(s) Groundwater Encountered: 7.00 ft. 2. 7 ft. 3. 5/23/00 ft.  
 WELL'S STATIC WATER LEVEL: 7.00 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 7 ft. after 5/23/00 hours pumping 10 gpm  
 Est. Yield 8 1/2 gpm Well water was 7 ft. after 5/23/00 hours pumping 10 gpm  
 Bore Hole Diameter: 8 1/2 in. to 7 ft., and 5 1/2 in. to 10 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped.  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded.  
 2 PVC 4 ABS 7 Fiberglass 7 PVC Threaded. X  
 Blank casing diameter 2 3/8 in. to 5 ft., Dia FLUSH MOUNT in. to SDR 13 ft.  
 Casing height above land surface: FLUSH MOUNT weight 7 PVC lbs./ft. Wall thickness or gauge No. Sch 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.  
 SCREEN-PERFORATED INTERVALS: From 10 ft. to 5 ft., From ft. to ft.  
 From 10 ft. to 4 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 4 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Heat cement 2 Cement grout 3 Bentonite 4 Other 4  
 Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 4 ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage 70  
 Direction from well? SOUTHWEST NORTHEAST How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.50	Grass-dk brn silty clay soil, moist, no odor.			
3.50	6	Red brn oxide stained clay, moist, no odor.			
6	8	Clive green clay w/ls.rx. chert gravel, moist to wet, faint odor.			
8	10	Weathered limestone to crystalline, hard, white/gray, dry.			
					Flush mt. ok'd by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-18-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 530 This Water Well Record was completed on (mo/day/yr) 7-5-00 under the business name of JB Environmental Drilling by (signature) James V. Becker