WATE	R WELL	RECORD	Form WWC-5	Di	vision of W	ater Reso	ources; App.	No		
1 LOCA	TION OF	WATER WELL:	Fraction SW 4 NE 4	VW 1/4	Section N	lumber	Township	Number 1 s	Range Number	
County: Marion SW ½ NE ½ NW ½ 7 T 21 S R 5 E Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)										
located within city? 502 Main St., Florence KS Latitude: N 38.24250°										
Longitude: W 96.92605° 2 WATER WELL OWNER: Shanklin Oil PP# St. Address Boy # 400 Witmersum West Dr. Datum: Shanklin Oil Shankli									2 37	
RR#, St. Address, Box # : 400 Witmarsum West Dr						Datum: above mean sea level				
City, State, ZIP Code : North Newton, Kansas, 67117-8086						Data Collection Method: legal survey				
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 30 ft.										
LOCA					MW2				•	
	I AN "X" I	N Depth(s) Groun	dwater Encountered 1		0 1 1 1	ft. 2		ft. 3	ft.	
SECT	SECTION BOX: WELL'S STATIC WATER LEVEL 9.21 ft. below land surface measured on mo/day/yr 6/17/6									
Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									ng gpm	
									niection well	
	1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below the supply 12 Other (Specify below the supply 12 Other (Specify below the supply 13 Other (Specify below the supply 14 Other (Specify below the supply 15 Other (Specify below th									
W 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (1) Monitoring well										
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs										
S Sample was submitted Water Well Disinfected? Yes No X										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded										
PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.28 ft., Weight lbs./ft. Wall thickness or gauge No.										
Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft.										
Casing height below land surface 0.28 ft., Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)										
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 12 ft. to 30 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.										
SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft. From ft. to ft.										
From ft. to ft. From ft. to ft										
GRAVEL PACK INTERVALS: From 12 ft. to 30 ft. From ft. to								o ft.		
From ft. to ft. From ft. to ft.									o ft.	
o droot wateral. I wat comon (2 comon ground between 4) one concrete.										
Grout Intervals From 2 ft. to 10 ft. From 10 ft. to 12 ft. From ft. to ft.										
What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify 2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)										
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well										
	from well?				y feet? ~3		West Bas II			
FROM	ТО	LITHO	LOGIC LOG	FROM	1 TO	T	PLUGG	ING INTE	ERVALS	
0	1	Concrete		25	30	Brown			low to moderate	
1	5		lay, moderate to high			plastic	ity, wet			
5	10	plasticity, moist	y clay, moderate to							
	10	high plasticity, mo		<u> </u>		+				
10	15		ty clay, moderate to						= D	
		high plasticity, mo					UKKI		בט	
15	25	Brown less gray si moderate plasticity				Fluck-	nount main	or from D	POW	
		moderate plasticity	, moist			riusnn	nount waiv	er from B	N	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged										
under my jurisdiction and was completed on (mo/day/year) 6/15/09 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed or (moday) year) 7/21/09 under the business name of Larsen & Associates, Inc. by (signature)										
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send and to WATER WELL OWNER and retain one for										
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.										