WATE	R WELL	RECORD Form WWC-5			er Resources: App. No.		
		WATER WELL: Fraction		Section Nur	mber   Township Number   Range Number		
County Marion NE & SE & NW & 7 T 21 S R 5 E  Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)							
llocated w	ithin city?	406 Main St., Florence, KS	i	Latituda	NI 29 241670		
				Longitude:	W 96.92569°		
		OWNER: Shanklin Oil		Elevation:	RIM: 1269.49; TOC: 1269.26		
		Box # : 400 Witmarsum West Dr		Datum:			
RR#, St. Address, Box # : 400 Witmarsum West Dr City. State. ZIP Code : North Newton. Kansas. 67117-8086 Data Collection Method: legal survey  3 LOCATE WELL'S   4 DEPTH OF COMPLETED WELL							
J LOCA	TON	L'S 4 DEPTH OF COMPLETED WELL	· ———	24	IL.		
WITH	I AN "X" I	N Denth(s) Groundwater Encountered		WI W 12	ft 2		
1	ION BOX:	WELL'S STATIC WATER LEVEL	7 05 f	t below land	ft. 2 ft. 3 d surface measured on mo/day/yr 1/6/10		
SECT	N	Pump test data: Well water w	1/1.93	t. ociow faire	ifter hours pumping gr		
	<del>-                                    </del>	Fst Yield onm: Well water w	vas 	ft a	efter hours numping ar		
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below							
W		E 2 Irrigation 4 Industrial 7 Domestic (	lawn &	garden) (10	Monitoring well		
-sw	/			· / C			
	Was a chemical/bacteriological sample submitted to Department? Yes No X: If yes, mo/day/yi						
S Sample was submitted Water Well Disinfected? Yes No X							
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Ste	eel	3 RMP (SR) 6 Ashestos-Cement 9	Other (	specify helo	w) Welded		
(2) PV	/C	4 ABS 7 Fiberglass	ouner (	speeily outo	Threaded Y		
Blank cas	ing diamete	er 2 in to 14 ft. Dia		in to	ft Dia in to		
Casing height helpw land surface 0.23 ft Weight lbs/ft Wall thickness or gauge No							
TVDE OF	Casing height below land surface 0.23 ft., Weight lbs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)							
ISCREEN OR DEPLOYATION OPENINGS ARE.							
2 Lo	uvered shut	tter 4 Key punched 6 Wire wrapped	MP (SR) 6 Asbestos-Cement 9 Other (specify below)  BS 7 Fiberglass Threaded X  2 in. to 14 ft., Dia in. to ft., Dia in. to ft.  Inface 0.23 ft., Weight Ibs./ft. Wall thickness or gauge No.  ERFORATION MATERIAL:  steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  ed steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)  FION OPENINGS ARE:  3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  INTERVALS: From 14 ft. to 24 ft. From ft. to ft.  From ft. to ft. From ft. to ft.  From ft. to ft.				
SCREEN-	PERFORA	TED INTERVALS: From 14	ft. to	24	ft. From ft. to		
		From	ft. to		ft. From ft. to		
GRAVEL PACK INTERVALS: From 12 ft. to 24 ft. From ft. to							
		From	ft. to		ft. From ft. to		
Grout Intervals From 2 ft. to 12 ft. From ft. to ft. From ft. to							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify							
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard  Direction from well? North  12 Fertilizer storage 15 Oil well/ gas well  How many feet? ~325 ft							
Direction	from well?	North H	ow many	/ feet? ~325	5 ft		
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0	1	Coarse limestone gravel with brick,					
1	1	brown silty clay matrix					
1	4	Dark brown silty clay, iron staining, moderate plasticity					
4	9	Silty clay with iron staining, dark brown		<del>                                     </del>			
		grading to brown, moderate plasticity					
9	14	Brown silty clay with very fine sand and					
1.4	3.	iron staining, moderate plasticity			71. (		
14	24	Gray-brown silty clay with very fine sand, iron staining, moderate plasticity		F	Flushmount waiver from BOW		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Donstructed, (2) reconstructed, or (3) plugged							
under my jurisdiction and was completed on (mo/day/year) 1/5/10 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No							
under the business name of Larsen & Associates, Inc. by (signature)							
INSTRUCT	TONS: Please	e fill in blanks or circle the correct answers. Send top thr	ee copies t	o Kansas Depa	artment of Health and Environment, Bureau of Water.		
vour records	your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.						
	NSTRUCTIONS. Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Deology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 6612-1367. Felephone "85-296-5522. Send onesto WATER WELL OWNER and retain one for our records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.						