KOLAR Document ID: 1578442

				WWC-5		vision of Wa			Wall ID		
U	Original Record Correction Change in Well Use LOCATION OF WATER WELL: Fraction				Resources App. No. Section Number Town			Township Numb	Well ID	aa Numbar	
1LOCATION OF WATER WELL:FractionCounty:1/41/41/41/41/4					1/4	ction NumberTownship NumberRange NumberTSR \Box EW					
						treet or Rural Address where well is located (if unknown, distance and					
						irection from nearest town or intersection): If at owner's address, check here:					
Address: Address:											
City:		State:	ZIP:								
3 LOCATE WELL WITH WY N 4 DEPTH OF COMPLETED WELL:						ft 5 Lati	tudo:			(desired deseas)	
WITH "A" IN Death(pth(s) Groundwater Encountered: 1)				5 Latitude:(decimal degrees) Longitude:(decimal degrees)				
SECTION N	BOX:	2) ft. 3) ft., or 4) 🗆 Dr					Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude:				
		WELL'S STATIC WATER LEVEL: ft.				Sour					
		 below land surface, measured on (mo-day-yr) above land surface, measured on (mo-day-yr) 					$\Box \text{ GPS (unit make/model:)}$				
NW	- NE	Pump test data: Well water was ft.					(WAAS enabled? □ Yes □ No) □ Land Survey □ Topographic Map				
w	XE	after hours pumping gpm					□ Online Mapper:				
SW -		Well water was ft.									
		after hours pumping gpn Estimated Yield:gpm				6 Elevation:ft. Ground Level TOC					
S		Bore Hole Diameter: in. to ft					Source: Land Survey GPS Topographic Map				
1 mil	le		ft.	□ Other							
7 WELL WATER TO BE USED AS:											
1. Domestic: 5. □ Public Water Supply: well ID □ Household 6. □ Dewatering: how many wells?											
☐ Househo ☐ Lawn &											
							al: how many bores				
2. 🗍 Irrigation						a) (a) Closed Loop 🔲 Horizontal 🗌 Vertical				
				-							
4. Industrial Recovery Injection 13. Other (specify):											
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted:											
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded											
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.											
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
Steel Stainless Steel Rress Columnized Steel											
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Image: Comparison of the second sec											
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify)											
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)											
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. to ft.											
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft. to ft. to ft.											
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other											
Nearest source of possible contamination: No potential source of contamination within 200 ft.											
Septic Ta			Lateral Line			Livestock F			ide Storage		
Sewer Li			Cess Pool	Sewage Lag		Fuel Storag			oned Water		
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well □ Other (Specify)											
Direction from well? ft.											
10 FROM	TO	I	ITHOLOG	GIC LOG	FROM	TO	LIT	HO. LOG (cont.) or	PLUGGIN	G INTERVALS	
├					-	-					
					Notes:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged											
under my jurisdiction and was completed on (mo-day-year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No											
Kansas Wate	r Well Con	tractor's Lice	ense No	This Wa	ter Well Re	ecord was co	omple	ted on (mo-day-ye	ear)		
	Siness name	Send one copy to	WATER W	ELL OWNER and retain o	ne for your re	cords. Fee of S	\$5.00 f	or each constructed we	<u></u> 11.		
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.											
Visit us at http	://www.kdhek	ks.gov/waterwel	l/index.html						KS	SA 82a-1212	