	WA	TER WELL REC	ORD Fo	rm WWC-5	KSA 82a	1212 ID N	o			
1 LOCATION OF WA	ATER WELL:	Fraction	NT	NE	Se	ction Number	1 3	Number	Range Number	
County: Coffey			NE 1/4			34	<u> </u>	22 _S	R 16E E/	W
Distance and direction 1950 N Main		wn or city street a	address of we	ell if located v	within city?					
2 WATER WELL OW	NER: 😿		awrence							
RR#, St. Address, Box	# :		N Main St.				Board of	f Agriculture, D	Division of Water Resour	rces
City, State, ZIP Code	:		, Ks.					ion Number:		
3 LOCATE WELL'S LO										
AN "X" IN SECTION N	BOX:	Depth(s) Groun	dwater Enco	ountered 1		ft	. 2	ft. 3	10-9-07	t.
1	x	Pur	no test data:	۷.د	was	ow land suriad	e measured on after	mo/day/yr	umping g	mar
NW	NE	Est. Yield3	gpm:	Well water	was	ft. a	after	hours p	umpingg	gpm
1444	- NE	WELL WATER				supply				
w !	<u>!</u>	1 Domestic 2 Irrigation			Dil field wate Domestic (la		9 Dewatering		other (Specify below)	
"	-				(12	s. gan com,				
sw -	- SE	Was a chemica	l/bacteriologi	ical sample s	ubmitted to	Department?	Yes No	X · If yes m	no/day/yrs sample was s	sub-
1	1	mitted	Daoionoiog	our ourripro o	dominiod to		ater Well Disinfe		No	Jub
S										
5 TYPE OF BLANK	CASING USED:		5 Wrought	iron	8 Concr	ete tile	CASING	JOINTS: Glue	d Clamped	
1 Steel	3 RMP (SI	R)	6 Asbestos			(specify below			ed	
2 PVC	4 ABS		7 Fiberglas	ss				Thre	aded	
Blank casing diameter		in. to 24		ft., Dia		in. to	ft.,	Dia	in. to	ft.
Casing height above la	and surface	····	in., weig	jht			lbs./ft. Wall thic	kness or guag	e No. •	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel			5 Fiberglas	29		7 <u>PVC</u> 8 RMP (SR)		Asbestos-Cem		
1 Steel 3 Stainless Steel 2 Brass 4 Galvanized Steel			6 Concrete tile			9 ABS		11 Other (Specify) 12 None used (open hole)		
SCREEN OR PERFOR	RATION OPENIN	NGS ARE:		5 Guaze	ed wrapped		8 Saw cut		11 None (open hole)	
1 Continuous slot		6 Wire wrapped			9 Drilled holes					
2 Louvered shutte	er 4 K	ey punched		7 Torch						
SCREEN-PERFORAT	ED INTERVALS:	From	29	ft. to	39	ft., From		ft. to		ft.
CDAVEL DA	CK INTERVALS	From2	σ	ft. to	.3.9	ft., From		ft. to		ft.
GRAVEL FA	OK INTERVALS	From		ft. to		ft., From		n. to ft. to		ft.
6 GROUT MATERIA		t cement	2 Cemer							
			20 ft., F	rom	ft.				ft. to	ft.
What is the nearest source of possible contamination:		7. Dit waters			10 Livestock pens		14 Abandoned water well			
1 Septic tank 4 Lateral lines		7 Pit privy		2000	11 Fuel storage12 Fertilizer storage		15 Oil well/Gas well _16 Other (specify below)			
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit			8 Sewage lagoon 9 Feedyard				ticide storage	dite	ditch	
	west	rage pit		3 reedyald		How mar		60		,
FROM TO		LITHOLOGIC	LOG		FROM	то	-	PLUGGING IN	TERVALS	
0 3	top soil									
3 6	brown cl									
6 15	grey cla									
15 22	brown cl									
22 24 24 37	brown fi									
24 37		and cher	t brown	n				-		
37 39	shale gr	ey								
									<u> </u>	
7 CONTRACTOR'S C	ANDOWNE	D'S CEPTIEICAT	TION: This :	rator wall wa	e (1) const	ucted (2) rese	anetruoted or /	a) plugged	der my jurisdiction and	was
completed on (mo/day/s	(ear)10-	9-07	IIOIV. IIIIS W	rater well wa	s (<u>i) constr</u>	ucteu, (∠) reco	cord is true to th	e best of my kr	der my jurisdiction and v gowledge and belief. Kan	wdS 1929
Water Well Contractor's	Licence No	1.8.2		This Water \	Nell Record	was complete	ed on (mo/day/vr	1	1-14-07	
under the business nan							(signature)	m Of	1950	
INSTRUCTIONS: Use type	ewriter or ball point pe	n. <i>PLEASE PRESS FI</i>	IRMLY and PRIN	T clearly. Please	fill in blanks, un	derline or circle the	correct answers. See	nd top three copies	to Kansas Department of Healt	th
	of Water, Geology Se			-, •						