GSI Job No. 047042 MW-2 WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number County: NW 1/4 SW 1/4 Chase NE 1/4 31 08 Ε Distance and direction from nearest town or city street address of well if located within city? I-35 Matfield Green Service Area, Mile Post 96 2 WATER WELL OWNER: **EL Paso Corporation** 2 North Nevada RR#, St. Address, Box # Board of Agriculture, Division of Water Resources Colorado Springs CO 80903 City, State, ZIP Code Application Number: LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 14 ft. ELEVATION: 1508.77 TOC AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 6.12 ft. below land surface measured on mo/day/yr 3-7-04 - NE ~ Pump test data: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 14 ft and Ε W Bore Hole Diameter **8** in. to **14** ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below) 1 Domestic 3 Feed lot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X CASING JOINTS: Glued Clamped 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush 2 PVC 4 ABS 7 Fiberglass 6 ft., Dia in. to ft., Dia in. to

nt in., weight 0.703 lbs./ft. Wall thickness or gauge No. Blank casing diameter 2 in. to Casing height above land surface Flushmount in., weight 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 5 Fiberglass 8 RMP (SR) 11 Other (specify)
6 Concrete tile 9 ABS 12 None used (open hole) 1 Steel Stainless steel 2 Brass 4 Galvanized steel 8 Saw cut 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 3 Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 7 Torch cut 10 Other (specify) 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From 6 ft. to 14 ft. From ft. to ft.
 From
 ft. to
 ft. From
 ft. to
 ft.

 From
 5
 ft. to
 14
 ft. From
 ft. to
 ft.

 From
 ft. to
 ft. From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: ft. From ft. to 3 Bentonite GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete

Grout Intervals From 0 ft. to 2 ft. From 2 ft. to 5 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 13 Insecticide storage 6 Seepage pit 9 Feedyard -----Direction from well? How many feet? LITHOLOGIC LOG FROM TO FROM PLUGGING INTERVALS 0 6 Gravelly silt and clay 6 <u>14</u> Limestone 용 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my juffsdiction and was

completed on (mo/day/yr)

3-7-04

and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No.

531

This Water Well Record was completed on (morday/yr)

3-15-04

under the business name of Geotechnical Services, Inc.

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.