

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>		<u>NE</u> 1/4 <u>NE</u> 1/4 <u>SW</u> 1/4	<u>17</u>	T <u>23</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>129 West Broadway, Newton, KS.</u>					
2 WATER WELL OWNER: <u>Kimball, Inc.</u>					
RR#, St. Address, Box #: <u>Rt2 Box 136 C</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>Halstead, KS. 67056</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>15'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>10'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>8.25</u> ft. below land surface measured on mo/day/yr <u>5-16-96</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2"</u> in. to <u>15'</u> ft. and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>No</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2.375</u> in. to <u>5'</u> ft. Dia in. to ft. Dia in. to <u>sdr 13</u> ft. Casing height above land surface <u>Flush Mt.</u> in. weight lbs./ft. Wall thickness or gauge No. <u>sch 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>15'</u> ft. to <u>5'</u> ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>15'</u> ft. to <u>4'</u> ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>4'</u> ft. to <u>3'</u> ft. From <u>3'</u> ft. to <u>0'</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>South</u> ③ ⑪ <u>East</u> How many feet? ③ <u>10'</u> ⑪ <u>225'</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Gravel			
.75	3	Dk brn silty clay, dry, firm to hard, low plasticity.			
3	7	Red brn oxide stained sandy clay, fine-med grained sand, moist to dry, earthy odor.			
7	11	Gray green olive weathered shaley clay, caliche, dry to moist, no odor, wet.			
11	15	Gray shale, hard, dry, tight, no odor.			
<u>F.M. OK'd by Don Taylor</u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-16-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>5-18-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					