

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 31 Township Number 23 Range Number 1

County: Harvey Distance and direction from nearest town or city street address of well if located within city? See blow

2 WATER WELL OWNER: Mark Hammond Board of Agriculture, Division of Water Resources

RR#, St. Address, Box #: 101 S. 24th W City, State, ZIP Code: Newton KS 67114 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section]

4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 10-11-96

Depth(s) Groundwater Encountered: 1. 16 ft. 2. 10-11-96 ft. 3. 10-11-96 ft.

WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 gpm: Well water was 11 in. to 66 ft. and 10-11-96 hours pumping

Est. Yield: 20 gpm: Well water was 11 in. to 66 ft. and 10-11-96 hours pumping

Bore Hole Diameter: 11 in. to 66 ft. and 10-11-96 in. to 10-11-96 ft.

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. to 31 ft. Dia. 2.40 in. to 160 ft. Dia.

Casing height above land surface: 160 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 31 ft. to 66 ft. From 16 ft. to 66 ft.

GRAVEL PACK INTERVALS: From 16 ft. to 66 ft.

6 GROUT MATERIAL: 1 Neat cement 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 16 ft. From 16 ft. to 66 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? South How many feet? 20

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-11-96 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-11-96

under the business name of Weninger Drilling Inc. by (signature) Michelle Becker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.