WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number County: Harvey NW 1/4 Pistance and direction from nearest town or city street address of well if located within city? Chris Wiebe/ Wiebe Tire 2 WATER WELL OWNER: 1107 S. Washington RR#, St. Address, Box # : Board of Agriculture, Division of Water Resources Newton, Ks. City, State, ZIP Code Application Number: LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL. ft. ELEVATION: AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVEL 13, \$5... ft. below land surface measured on mo/day/yr 5.714. Pump test data: Well water was ft. after hours pumping gpm NW NE --Est. Yield gpm; Well water was , ft. after hours pumping gpm Bore Hole Diameter ... 8/5" in. to .20' ft., and in. to ft. W 5 Public water supply WELL WATER TO BE USED AS: 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only (10) Monitoring well 2 Irrigation 4 Industrial Was a chemical/bacteriological sample submitted to Department? Yes..........No. X......; If yes, mo/day/yr_sample was submitted Water Well Disinfected? Yes TYPE OF BLANK CASING USED: CASING JOINTS: Glued Clamped 5 Wrought iron 8 Concrete tile 1 Steel 3 RMP (SR) Welded 6 Asbestos-Cement 9 Other (specify below) 2 PVC 7 Fiberglass Threaded. Blank casing diameter ft., Dia in. to ft., Dia in. to SDR .13.... ft. Casing height above land surface FULAN Mt. Ibs./ft. Wall thickness or gauge No. . . SCh . 40in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: Z PVC 10 Asbestos-cement 8 RMP (SR) 1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 9 ABS 6 Concrete tile 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 3 Mill slot 1 Continuous slot 6 Wire wrapped 9 Drilled holes 4 Key punched 7 Torch cut 2 Louvered shutter 10 Other (specify) SCREEN-PERFORATED INTERVALS: ft. to ft., From From. 20 ft. to . GRAVEL PACK INTERVALS: ft. to . From / 3 Bentonite 6 GROUT MATERIAL: (2) Cement grout 1_Neat cement # to 4 From. ft., From What is the nearest source of possible ontamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage Former 15 Oil well/Gas well 5 Cess pool 2 Sewer lines 12 Fertilizer storage 8 Sewage lagoon 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? 300 FROM LITHOLOGIC LOG FROM PLUGGING INTERVALS TO 0 .50 Gravel .50 Dk brn clay, moist, no odor. 8 Pale gray silty sandy clay, moist, firm, poorly sorted. 12 15 Lt gray mottled clay w/ caliche layers & nodules, firm, no odor. 15 20 Lt gray sandy clay w/ caliche nodules, fine grained sand, no odor, low-med plasticity Flush mt. OK'd by Don Taylor 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . 5.14-4-1. and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-21-1...

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or

by (signature

under the business name of JB Environmental Drilling