USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740

| | | | | | | Topeka, Kansas 60020 | | | | |
|--|----------|-------------------------|----------|-------|---------|----------------------|---|--|---|-------|
| | County | Township name | Fraction | | | n number | _ | Town number | Range number | |
| 1 Location of well: | HARVEY | Newton | 34/4/ | SE1/4 | 1 | | -5 | T-23-5 | R-15 | |
| Distance and direction from nearest town or city: 1 3 Owner of well: HAROLE 6 HOSS | | | | | | | | | | |
| Street address of well location if in city: | | | | | ddress: | | | E 24th St. N. Newton trus | | |
| Locate with "X" in section below: Sketch map: | | | | | | | 4 Well depth: 39 ft. Date of completion 5/22/75 Well diameter 12" in. | | | |
| | | | | | | - | 5 Cable tool X Rotary Driven Dug | | | |
| | | | | | | | Hollow rod Jetted Bored Reverse rotary | | | |
| w | | | | | | | 6 Use: Domestic Public supply Industry Domestic Public supply Commercial | | | |
| | | | | | | ŀ | 7 Ca | sing: Material Puc | Height: 6600/below | |
| <u> </u> | | | | | | | Threaded Welded NiSurface Lain. | | | |
| S Mile | | | | | | | Diam. 6# Weight | | | |
| 2 | <u> </u> | e and color of material | <u>-</u> | | From | То | | in. toft. depth | | |
| | | e and color of indicate | | | 110111 | | | reen: PP M41 anufacturer <u>OWN</u> | - Germmeed | |
| Logn | | | | | 0 | 5 | Ту | pe | Dia6" | |
| Il to lieux by class | | | | | 5 | 15 | | ot/gauze <u>6046</u> t between <u>74</u> ft. and | | |
| the state of the s | | | | | /2 | バー | Fi | | 118-31011 | |
| Sant Mes Size | | | | | | 75 | | atic water level: | 312e range of material — | |
| Sant course | | | | | 15 | 22 | | ft. below land surface | e Date 5/22/25 | |
| | guey- | gueen s | Shole | | 22 | 25- | | mping level below land su | rfaces: pumping 20 g.p.m. | |
| hight Snev Shale | | | | | 25 | 30 | _ | ft. after hrs | pumping g.p.m. | |
| dank blk style | | | | | 30 | 39 | | rimated maximum yield ater sample submitted: | g.p.m. | |
| White Line Stone | | | | | 35 | ' | | <u> </u> | te | |
| White sime stone | | | | | | | 1 — | ell head completion: Pitless adapter | Inches above grade | |
| | · | | <u> </u> | | | | 13 W | ell grouted? 🔀 Yes | □ N ₀ | i |
| | | | **** | | | | ڪري De | Neat cement Benton | LO_ft. | |
| | | | | | | | 14 N | earest source of possible of | ontamination: | Kerra |
| | | | | | | | | ell disinfected upon comp | | Pewer |
| | | | | | | | 15 Pu | | Not installed | |
| | | | | | | | ~ | anufacturer's name | HPSD-12 50/olts 230 ft. capacity /2 g.m.p. | |
| | | | | | | | 4 | rngth of drop pipe 35 | ft. capacity 2 g.m.p. | |
| | | | | | | | | Submersible | Turbine | |
| (use a second sheet if needed) | | | | | | | |] Jet] Certrifugal | Reciprocating Other | |
| 16 Remarks: elevation | | | | | | | 1 | ater well contractor's cert | | |
| | | | | | | | 1 | is well was drilled under r port is true to the best of r | | |
| Topography: | | | | | | | l | DAULK TA | 14 # 175 | |
| ☐ Hill ☐ Slope | | | | | | | | siness name ddress Box 26 | Hrostan K | · u |
| ☐ Ūpland | | | | | | | Si | gned Authorited repres | Date 5/22 | 75 |
| Valley | | | | | | | | , | | J |