


1 LOCATION OF WATER WELL: County: HARVEY Fraction: SW 1/4 NE 1/4 SW 1/4 Section Number: 5 Township Number: T 23 S Range Number: R 1-E EW

Distance and direction from nearest town or city street address of well if located within city?
2914 BLUESTEM CT.

2 WATER WELL OWNER: Mike Schmidt
 RR#, St. Address, Box #: 2914 Bluestem Ct.
 City, State, ZIP Code: North Newton, Kansas
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 68' ft. ELEVATION: FLAT
 Depth(s) Groundwater Encountered 1. 50 ft. 2. 50 ft. 3. 50 ft.
 WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on 5-15-90 mo/day/yr
 Pump test data: Well water was 60 ft. after 1 hours pumping 10 gpm
 Est. Yield 10 gpm: Well water was 60 ft. after 1 hours pumping 10 gpm
 Bore Hole Diameter: 9 in. to 68 ft., and 68 in. to 68 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 0 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 0.5 in. to 48 ft., Dia. 48 in. to 48 ft., Dia. 48 in. to 48 ft.
 Casing height above land surface: 24 in., weight 1.29 lbs./ft. Wall thickness or gauge No. 1.214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 0
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 0 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 0
 SCREEN-PERFORATED INTERVALS: From 48 ft. to 68 ft., From 48 ft. to 68 ft., From 48 ft. to 68 ft.
 GRAVEL PACK INTERVALS: From 14 ft. to 68 ft., From 14 ft. to 68 ft., From 14 ft. to 68 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0 ft. to 14 ft., From 0 ft. to 14 ft., From 0 ft. to 14 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? WEST How many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>25</u>	<u>CLAY</u>			
<u>25</u>	<u>30</u>	<u>FINE SAND CLAY MIX</u>			
<u>30</u>	<u>50</u>	<u>CLAY</u>			
<u>50</u>	<u>68</u>	<u>SHALE - BLUE</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-15-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 302 This Water Well Record was completed on (mo/day/yr) 5-15-90 under the business name of MARTINSUPPLY by (signature) Mike Schmidt

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.