

1 LOCATION OF WATER WELL: County: Harrey Fraction: Se 1/4 Ne 1/4 NW 1/4 Section Number: 8 Township Number: T 23 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city?
In City Newton 1817 Windsor Dr.

2 WATER WELL OWNER: Earl Stubby
 RR#, St. Address, Box #: 1817 Windsor Dr. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Newton, KS, 67114 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	X	NE
W			E
	SW		SE
		S	

4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 1275 ft.
 Depth(s) Groundwater Encountered 1. 1275 ft. 2. 48 ft. 3. 2-4-88
 WELL'S STATIC WATER LEVEL 1275 ft. below land surface measured on mo/day/yr 2-4-88
 Pump test data: Well water was 15 gpm. Well water was 9 ft. after 48 hours pumping 15 gpm
 Est. Yield 15 gpm. Well water was 9 ft. after 48 hours pumping 15 gpm
 Bore Hole Diameter 9 in. to 48 ft., and 9 in. to 48 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 1230 ft., Dia. 5 in. to 48 ft., Dia. 5 in. to 48 ft.
 Casing height above land surface 1230 in., weight CLASS 160 lbs./ft. Wall thickness or gauge No. 214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7 PVC
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 30 ft. to 40 ft.
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From 23 ft. to 48 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 48 ft., From 23 ft. to 48 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft., From 3 ft. to 23 ft., From 3 ft. to 23 ft., From 3 ft. to 23 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? E How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay			
3	12	fine Sand			
12	23	Clay			
23	35	Medium Sand			
35	48	Blue Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-4-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 180 This Water Well Record was completed on (mo/day/yr) 2-17-88 under the business name of Backhus Drilling by (signature) Paul Backhus

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4