	WATER	WELL RECORD	Form WWC-5	KSA 82a-			
LOCATION OF WATER WELL:	Fraction	NW 1/4 SE		on Number	Township Num	- 1	Range Number
ounty: Toward direction from pogrest tow	DE 1/4	10 1 17			⊤ 23	S	R I E/S
vistance and direction from nearest tow	n or city street addi	ess of well if locate	a within city?				MW-ZD
May East 5	cc 0.1.						mw 20
WATER WELL OWNER: AT	or racinga	~~					
R#, St. Address, Box # : 1/2 1					Board of Agr	iculture, Divis	ion of Water Resource
ity, State, ZIP Code : New to			7		Application N		
LOCATE WELL'S LOCATION WITH	DÉPTH OF COM	PLETED WELL		. ft. ELEVAT	10N:		
AN "X" IN SECTION BOX:	Depth(s) Groundwa	ter Encountered	RT_{α}	, ft. 2.		ft. 3	
!	WELL'S STATIC W	ATER LEVEL].	. 2.6 ft. be	low land surfa	ace measured on n	no/day/yr	
NW - NE	Pump te	est data: Well wate	erwas	ft. aft	ter	hours pumpii	ng gpm
							ng gpm
w i E	Bore Hole Diamete	r 💍in. to	10	ft., a	nd	in. to	
W	WELL WATER TO	BE USED AS:	5 Public water	, , ,	8 Air conditioning	,	ction well
tu Xt	1 Domestic	3 Feedlot			Dewatering		
sw se	2 Irrigation	4 Industrial	7 Lawn and ga	arden only 1	 Monitoring well . 		
	Was a chemical/bad	teriological sample	submitted to De	partment? Ye	sNo	,; If yes, mo	/day/yr sample was sut
S	mitted			Wat	er Well Disinfected	Yes	No X
TYPE OF BLANK CASING USED:	5	Wrought iron	8 Concret	e tile	CASING JOIN	TS: Glued	Clamped
	R) 6	Asbestos-Cement	9 Other (s	specify below)	Welded.	
(2)=VC A ABS	7	Fiberglass				Threaded	ı X
lank casing diameter	in, to	ft., Dia 🚄 .	in. to .		ft., Dia	in. [.]	to ft.
Casing height above land surface	O in	., weight	0.3	lbs./f	t. Wall thickness or	gauge No	
YPE OF SCREEN OR PERFORATION	MATERIAL:		(7)PVC	;	10 Asbes	stos-cement	
1 Steel 3 Stainless	steel 5	Fiberglass	8 RMF	P (SR)	11 Other	(specify)	
2 Brass 4 Galvanize	ed steel 6	Concrete tile	9 ABS		12 None	used (open	hole)
CREEN OR PERFORATION OPENING	GS ARE:	5 Gauz	red wrapped		8 Saw cut	11	None (open hole)
1 Continuous slot (3 Ni	II slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shutter 4 Ke	ey punched	7 Torcl	n cut_		10 Other (specify)		
CREEN-PERFORATED INTERVALS:	From	ft. to .	20	ft., Fron	n	ft. to	
	From	ft. to .	<u></u>	ft., Fron	n	ft. to	
GRAVEL PACK INTERVALS:	From	ft. to .	26	ft., Fron	n	ft. to	
_	From	ft. to	_	ft., Fron			ft.
GROUT MATERIAL: (1) Neat of	ement 2	Cement grout	. (3) Bentor	nite 4	Other		
Grout Intervals: From	ft. to	ft., From	<i>].</i> ft t	۵ گ	ft., From	1	ft. to
What is the nearest source of possible	contamination:			10 Livest	ock pens	14 Aban	doned water well
1 Septic tank 4 Latera	al lines	7 Pit privy		11 Fuel s	storage	15 Oil w	ell/Gas well
2 Sewer lines 5 Cess	pool	8 Sewage lag	joon	12 Fertili:	zer storage	16 Other	(specify below)
3 Watertight sewer lines 6 Seep	age pit	9 Feedyard		13 Insect	icide storage .		
Direction from well? WITTEN 1	railyand			How mar	ny feet?		
FROM TO	LITHOLOGIC LC)G	FROM	ТО	PLU	GGING INTE	RVALS
0 5 Concr	ill						
15 2 Fill		ΔΔ		1			
2 19.5 Sandy	clay -d	curen sand					
9.5 20 Sando	0)) - '					
				1			
CONTRACTORS OF LANDOWNER	DIS CERTIFICATION	U. This		l	potruoted of (0) =1:	lagod under	my juriediation and
CONTRACTOR'S OR LANDOWNER	13 CERTIFICATIO	I LIQUE					
ompleted on (mo/day/year)	102 de	J. 1				77. KBW	edge and belief. Kansa
Vater Well Contractor's License No.	1 1000	This Water	Well Record was	•	/ // //	DITHIH	11
nder the business name of	myne 1 0	, ,		by (signat		- Jun	
INSTRUCTIONS: Use typewriter or ball point of Health and Environment, Bureau of Water,							es to Kansas Department