LOCATION OF WATER WAY	FRACTION	Water Well Record		A 82a-1212	TU-N	Par No	
LOCATION OF WATER WELL:		NP ML		ion Number 18	Township Number	Range Number	
Harvey  Distance and direction frem nearest town	NE 1/4 or city street address of well if loca	NE 1/4 NW ted within city?	1/4	10	т 23 s	R 1E EW	
621 Trinity Newton, Kansas							
2 WATER WELL OWNER: KOLAND, Lance							
13	1 Trinity				Board of Agriculture, Di	vivsion of Water Resource	
	wton, Kansas				Application Number	*:	
J LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COM		60 n	-	ATION:		
AN "X" IN SECTION BOX:	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
	WELL'S STATIC W.				ACE MEASURED ON mo/day/yr	06/08/1994	
Pump test data: Well water was ft. after hours pumping gpm  Est. Yield gpm: Well water was ft. after hours pumping gpm							
<b>a</b>	Bore Hole Diameter	91	60	ft. ai	and in.	ping gpm to ft.	
w w	WELL WATER TO I		ublic water supp			njection well	
	1 Domestic		Dil field water su	. •		ther (Specify below)	
SW SE	2 Irrigation	4 Industrial 7 I	awn and garden	only 10	Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No 🗶 ; If yes, mo/day/yr sample was							
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded 2 DN/C 4 ABS 7 Fiberglass CDD 26 Threaded							
2 PVC 4 ABS		7 Fiberglass	SDR-				
Blank casing Diameter 5	in. to 35	ft., Dia	in. to 35 lbs./		ft., Dia in.	to ft.	
Casing height above land surface TYPE OF SCREEN OR PERFO		weight 2.	7 PVC		'all thickness or gauge No. 10 Asbestos-ceme	.214	
1 Steel 3 Stainless S		5 Fiberglass	8 RMF		11 other (specify	)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						en hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS: from 35 ft. to 60 ft., From ft. to							
from		ft. to	•	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24		ft. to	o 60	ft., From	ft. to	ft.	
from ft. to ft., From ft. to ft.  GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
What is the nearest source of possible contamination:		ft. From	ft. to	10 Livestocl	ft. From k pens 14 A	ft. to ft. Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel stor	rage 150	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize	r storage 16 (	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? East					How many feet? 25		
FROM TO	LITHOLOGIC LOG		FROM	то	PLUGGING INTE	RVALŞ	
0 3 topsoi					· · · · · · · · · · · · · · · · · · ·		
3 35 clay 35 45 fine s	· and	,					
45 60 grey s							
ATON S							
	177						
		44.				74	
-							
		AB-Value					
	- An		-70-22				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No236							
Under the business name of Harp Well & Pump Service, Inc. by (signature)							
Jane Frederick							