

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	NW 1/4 SW 1/4 SW 1/4	21	T 23 S	R 1 <u>EA</u>

Distance and direction from nearest town or city street address of well if located within city?

1100 S. Kansas Street, Newton, KS MW 5

2 WATER WELL OWNER:	City of Newton
RR#, St. Address, Box # :	Box 426
City, State, ZIP Code :	Newton, KS 67114
Board of Agriculture, Division of Water Resources	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 17 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 16.12 ft. below land surface measured on mo/day/yr 07-01-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 5/8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 9 ft., Dia			Threaded X
Casing height above land surface 0 in., weight			lbs./ft. Wall thickness or gauge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	2 Mill slot	3 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 9 ft. to 29 ft., From			
GRAVEL PACK INTERVALS:			
From 7 ft. to 29 ft., From			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 1.5 ft., From				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? West			13 Insecticide storage	
			How many feet? 120	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6 "	Concrete			
6"	6 '	Clay, dark brown			Flush Mount Cover
6	7	Clay, reddish tan			
7	9	Clay, whitish tan			KDHE Site ID # 00097622
9	15	Sand, grey, very fine to fine			
15	23	Sand, green, fine to medium			
23	29	Sandy clay, green			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-24-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 07-07-92 by (signature) Dale Holt
under the business name of GeoCore Services, Inc