

1 LOCATION OF WATER WELL:		Fraction	SW 1/4 SW 1/4 NE 1/4	Section Number	29	Township Number	T 23 S	Range Number	R 1E 1W
Distance and direction from nearest town or city street address of well if located within city? 1/2 So. of Highway 50, 1 W. of Broadway, 1 So. of Newton, Kansas									
2 WATER WELL OWNER:		Jack Graham 2416 West 60th North Wichita, Kansas							
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources							
City, State, ZIP Code :		Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL . 68 . ft. ELEVATION: ft.							
		Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL . 15 ft. below land surface measured on mo/day/yr . 1-3-83							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter . 11 in. to ft., and in. to ft.							
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well							
Was a chemical/bacteriological sample submitted to Department? Yes No . X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded							
Blank casing diameter . 5 in. to . 20 ft., Dia in. to ft.		Cer-Mac Styrene SDR-26 in. to ft.							
Casing height above land surface . 12 in., weight . 1.59 lbs./ft. Wall thickness or gauge No. . 203									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From . 20 ft. to . 68 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		From . 14 ft. to . 68 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From . 4 ft. to . 14 ft., From ft. to ft.							
What is the nearest source of possible contamination:		None Apparent 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG			
0	3	Topsoil							
3	6	Clay							
6	68	Gray Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . 1-3-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. . 236 This Water Well Record was completed on (mo/day/yr) . 3-28-83 under the business name of Harp Well & Pump Service, Inc. by (signature) M. Arnold									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									