l lana			TRA CTION	Water Well Record	Form WWC-5	KSA 82a-1212					
1 LOCA		ATER WELL:	FRACTION			Section Number	Township Numbe	r	Range Number		
Distance	Harve		NW 1/4		TW 1/4	23	т 23 ;	S	R 1E E/W	<u> </u>	
1			t of I-35,	. •	F 1		Marchan	V			
	TER WELL		TON, CITY (e or re	st st.	Newton,	Name	18	_	
RR#,	ST. ADRESS		. Box 687	,,,		Board of Agriculture, Divivsion of Water Resource					
CITY, STATE, ZIP CODE: Newton, Kans				67114			Application Number: 990026				
		LOCATION WITH	4 DEPTH OF CO	MPLETED WELL	25	ft. EL	EVATION:				
AN "X	" IN SECTIO	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2	ft.	3 ft	4	
 	X		WELL'S STATIC W		5 FT.	BELOW LAND SI	JRFACE MEASURED ON	mo/day/yr	02/03/199	9	
	NW	NE	Pump tes		water was	ft.		hours pump		pm	
<u> </u>			Est. Yield	91	water was	ft.		hours pump		pm	
1₹ M	/ 	E	Bore Hole Diameter WELL WATER TO	12 in.	to 25 5 Public water	ft.	and	in. 11 7	to f jection well	ft.	
			1 Domestic		6 Oil field wat		8 Air conditioning 9 Dewatering	7-	her (Specify below)		
	sw		2 Irrigation		7 Lawn and ga		10 Monitoring well		(
]			1	eriological sample su	le submitted to Department? Yes No X ; If yes, mo/day/yr sample was						
		S	submitted				nter Well Disinfected?				
5 TY	PE OF CA	ASING USED:		5 Wrought iron	8 (Concrete tile	CASING JOIN	NTS: Gli	1ed X Clamped		
1 Steel 3 RMP (SR) 6 Asbestos-Cement						9 Other (Specify below) Welded					
2 PVC	C	4 ABS		7 Fiberglass	SI	DR-26		Th	readed		
1	asing Dian	-	in. to 20	ft., Dia	in.	to	ft., Dia	in.	to ft.		
-	•		1.2 in. , ATION MATERIAL:	weight 2		lbs. / ft.	Wall thickness or ga		.214		
1 Ste		3 Stainless Steel	IIION MATERIAL:	5 Fiberglass		7 PVC 10 Asbestos-cement 8 RMP (SR) 11 other (specify)					
2 Bra		4 Galvanized ste	el	6 Concrete tile		ABS		one used (ope	n hole)		
2 Diano Tomande Secti					ed wrapped		8 Saw cut	11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire w						9 Drilled holes				,	
2 Louve	ered shutte			7 Torch	ı cut		10 Other (specif	fy)			
SCREE	N-PERFO	RATION INTER	VALS: from 20		to 25	ft., Fro	n	ft. to		ft.	
			from		to	ft., Fro		ft. to		ft.	
GRAVEL PACK INTERVALS: from 20					. to 25 ft., Fro		ft. to			ft.	
<u> </u>	,		from	ft.	to	ft., Fro		ft. to		ſŧ.	
	DUT MAT	2241221		Cement grout	3 Ben	tonite	4 Other				
Grout Intervals: From 0 ft. to 20 ft. From						4071				ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy						10 Livestock pens 11 Fuel storage			14 Abandon water well		
2 Sewer lines 5 Cess pool 8 Sewage la					on		izer storage	15 Oil well/Gas well 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard						13 Insecticide storage None Apparent					
•	on from we	-	age pie				How many feet?		Apparenc		
FROM		<u> </u>	LITHOLOGIC LOG		FROM	TO		ING INTER	VALS		
0	3	topsoil									
3	11	clay									
11	18	fine sar	nd								
18	19	clay									
19	25	fine sar	na			-					
	.										
<u> </u>	_					 					
 	ļ	ļ									
.						 					
	<u> </u>	1	·			<u> </u>					
	NTRACTO	OR'S OR LANDOWNI	er's certification: Th	nis water well was (1) constructe	ed, (2) reconst	ructed, or (3) plugg	ed under m	y jurisdiction and		
			r) 02/03/ 236							er	
Under	ontracto r the buei	ness name of H	arp Well &	Pump Serv	ice. In	C by (sin	nay, y: / nature)		·/··//··//···		
3.746		OIMN			a		To	dd S	. Harp		