1 LOCATION OF WATER WELL:	FRACTION	Water Well Recor	rd Form WWC-	KSA 82a-1212 Section Number		· · · · · · · · · · · · · · · · · · ·	
Harvey	NW 1/4	NE 1/4	NW 1/4	23	Township Number		Range Number
Distance and direction frem nearest town or city stre	<del></del>		TAM 1/4		T 23 s	<u>l</u>	R 1E EW
1 1/2 miles East of I-35, South side of 1st St. Newton, Kansas							
WATER WELL OWNER: NEWTON, CITY OF							
RR#, ST. ADRESS, BOX#: P.O. E					Board of Agriculture, Divivsion of Water Resource		
CITY, STATE, ZIP CODE: Newtor	ı, Kansas			67114	Appli	cation Number: 9	90026
AN UVU DI SECTION DOV.		IPLETED WELL	25		EVATION:		
	Depth(s) groundwa		1	ft.	2	ft. 3	ft.
	LL'S STATIC W. Pump test	ATER LEVEL 1	b F1 water was		RFACE MEASURED ON		/03/1999
NW NE NE Fet	Yield		water was	ft. ft.		ours pumping ours pumping	gpm
l e l l Por	e Hole Diameter	12 in.	to 25	ft.	and	in. to	gpm ft.
E WE	LL WATER TO I		5 Public water		8 Air conditioning	11 Injectio	
	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering	12 Other (	Specify below)
	2 Irrigation	4 Industrial	7 Lawn and g	garden only	10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was							
Su	bmitted				ter Well Disinfected?	Yes X	No
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Ceme		Concrete tile	CASING JOIN	91404	X Clamped
2 PVC 4 ABS		7 Fiberglass	-	Other (Specify b	elow)	Welded Thread	
Blank casing Diameter 5 in.	to 20	ft., Dia	in.	DR-26	ft., Dia	in. to	
Casing height above land surface 12	in.,	weight 2			Wall thickness or gau		ft. .214
TYPE OF SCREEN OR PERFORATION		ŭ	,	7 PVC		estos-cement	.211
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 oth	er (specify)	
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS		ne used (open ho	•
SCREEN OR PERFORATION OPENIN	G ARE:		zed wrapped		8 Saw cut	11	None (open hole)
1 Continuous slot 3 Mill slot	- 3		e wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punch		7 Toro			10 Other (specif	y)	_
SCREEN-PERFORATION INTERVALS	20		. to 25	ft., Fron		ft. to	ft.
GRAVEL PACK INTERVAL	from S: from 20		t. to t. to 25	ft., Fron		ft. to	ft.
GRAVEL FACK INTERVAL	s: Irom ∠∪ from		ւ to <u>Հ</u> յ	ft., Fron ft., Fron		ft. to ft. to	ft. ft.
6 GROUT MATERIAL: 1 Neat ceme		ement grout		ntonite	4 Other	14 10	
Grout Intervals: From 0 ft.	to 20	ft. From	ft.	to	ft. From	ft.	to ft.
What is the nearest source of possible contamination:				10 Livesto	ock pens	14 Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel st	•	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage 13 Insecticide storage		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage p	it	9 Feedyard			J	None Ap	parent
Direction from well?   FROM   TO   LITI	HOLOGIC LOG		FROM	ТО	How many feet? PLUGGI	NG INTERVAL	s
0 3 topsoil							
3   11   clay							
11 18 fine sand							
18 19 clay							
19 25 fine sand				1			
					,		
				-			
<b> </b>							
7			<u> </u>				- J: A:
ONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Under the business name of Harp Well & Pump Service. Inc. by (signature)							
Todd S. Harp							