	W	ater Well Record Form WW	C-5 KSA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION Center	Of Lu Y2	Section Number	Township Number	Range Number
Harvey	Lenier 1/4	1/4 1/4	19	T 23 S	R 1E E/W
Distance and direction frem nearest town or city str	eet address of well if located within	n city?			
Meridian & Hwy 50, 1/	² m. N., 1/4 E	., S. side of	Sharps	Newton, Kansas	
WATER WELL OWNER: NEWTON,	CITY OF				
RR#, ST. ADRESS, BOX #: P.O. Bo				Board of Agriculture, D	ivivsion of Water Resource
CITY, STATE, ZIP CODE: Newton,	, Kansas		67114	Application Numbe	r: 20020008
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETI		ft. ELE	EVATION:	
N	Depth(s) groundwater En		ft.	2 ft.	3 ft.
	ELL'S STATIC WATER	LEVEL 16	FT. BELOW LAND SU	RFACE MEASURED ON mo/day/yr	1-16-2002
NW NE	Pump test data:	Well water was	ft.	after hours pum	ping gpm
<u>s</u> Est.	. Yield gpm:	Well water was	ft.	after hours pum	ping gpm
	e Hole Diameter 12	in. to 35	ft.	and in.	to ft.
- WE	CLL WATER TO BE USE			•	njection well
SW SE	1 Domestic 3 Feed				Other (Specify below)
	- mganon		_	0 Monitoring well	
e l'	is a chemical/bacteriologic	cal sample submitted t	•		io/day/yr sample was
5 TYPE OF CASING USED:	bmitted			er Well Disinfected? Yes	
1 Steel 3 RMP (SR)		ought iron estos-Cement	8 Concrete tile		lued Clamped
()			9 Other (Specify b SDR-26	· ·	Velded Threaded
2 PVC 4 ABS		S			
Blank casing Diameter 5 in.	,	Dia i weight 2.35	n. to	ft., Dia in.	to ft.
Casing height above land surface 12 TYPE OF SCREEN OR PERFORATIO	in. , ON MATERIAL:	weight 2.35	lbs. / ft. 7_ <u>PVC</u>	Wall thickness or gauge No. 10 Asbestos-ceme	
1 Steel 3 Stainless Steel	5 Fiber	rglass	8 RMP (SR)	11 other (specify	
2 Brass 4 Galvanized steel	6 Conc	rete tile	9 ABS	12 None used (on	
SCREEN OR PERFORATION OPENING ARE: 5 Gauze			ed	8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire w			· -	9 Drilled holes	
2 Louvered shutter 4 Key punch	ied	7 Torch cut		10 Other (specify)	
SCREEN-PERFORATION INTERVAL	S: from 20	ft. to 35	ft., From	`•	ft.
_		ft. to	ft., From		
- 1		ft. to 35	ft., From		ft.
		ft. to	ft., From		ft. ft.
6 GROUT MATERIAL: 1 Neat ceme	ent 2 Cement g	rout 3 I	Bentonite	4 Other bentonite h	
Grout Intervals: From ft.	to ft.	From f	t. to	ft. From 0	ft. to 20 ft.
What is the nearest source of possible contamination:			10 Livestock pens 14 Abandon water well		
		Pit privy	11 Fuel ste	- 13 (Dil well/Gas well
o Centra provi		Sewage lagoon	**		Other (specify below)
3 Watertight sewer lines 6 Seepage 3	oit 9	Feedyard	13 Insection	cide storage None	Apparent
Direction from well?				How many feet?	
FROM TO LITI	HOLOGIC LOG	FROM	4 TO	PLUGGING INTE	RYALS
3 17 clay					
17 24 fine sand					
24 35 grey shale				TO THE RESERVE AND ADDRESS OF THE RESERVE OF THE RE	
3-7					
	- united to a				
					PROTECT - Aller of Management and Company of the Co
					White Andrews is in the advantage over the second of the s

		·			
7 CONTRACTOR'S OR LANDOWNER'S C	EPTIFICATION. This water	r well was (1) const	ructed (2) recons	tructed or (3) plugged upde	r my juriediction and
was completed on (mo/day/year)	1-16-2002	and th	is record is true t	o the best of my knowledge	and belief Kanese
Water Well Contractor's License No	236	This Water Well Re	cord was comple	ted on	and bonor. Ransas
(mo/day/yr)1-21-2002	•••••				
Under the husiness name of Ha	rp Well & Pump	Service, Inc	by 6	signature) Lodd	S Hara