				Water 11	Iell Decord	Form WWC 5	VCA 92- 1212					
1 LOCATION OF WATER WELL: FRACTION			ter of w 12			Section Number	KSA 82a-1212 Section Number Township N		umber Range Number			
Harvey Cen			er Ut	, W	1/4	19	T 23	S	, 1E	E/W		
Distance and direction frem		•		·						<u> </u>		
Meridian & Hwy 50, 1/2 m. N., 1/4 E., S. side of Sharps Newton, Kansas												
WATER WELLOWNER: NEWTON, CITY OF												
RR#, ST. ADRESS, BOX		Box						Bos	rd of Agriculture, Di	ivivsion of Water I	Resource	
CITY, STATE, ZIP COD			ansas				67114		Application Number	r: 200200	908	
LOCATE WELL'S LOCATE AN "X" IN SECTION BOX			PTH OF CO			32		LEVATION:				
l N	——————————————————————————————————————	-	th(s) groundw			1	ft.	2	ft.	3	ft.	
	WELL'S STATIC V				4 data.				SURFACE MEASURED ON mo/day/yr 1-16-2002			
NW	NE	Est. Yie	-				ft.	after	hours pum	. 0	gpm	
w X			eiu ole Diameter	gpm: 12		iter was	ft.	after	hours pum		gpm	
≥ w ∧	E		WATER TO			Public wate	ft. r supply	and 8 Air conditioni	in. 11 I.	to ijection well	ft.	
			omestic	3 Feedlot		Oil field wa		9 Dewatering		ther (Specify	helow)	
sw	SE	2 Ir	rigation	4 Industri			arden only	10 Monitoring w		ener (opeen)	<i>below</i> ,	
		Was a c	hemical/bact	eriological sa	ample sub	mitted to D	epartment? Ye	· ·	X ; If yes, m	o/day/yr sami	ole was	
S		submit					•	ater Well Disinfe				
5 TYPE OF CASING	G USED:			5 Wrough	nt iron	8	Concrete tile	CASING.			nped	
1 Steel 3 RMP (SR)				•			Other (Specify	below)	Welded			
2 PVC	4 ABS			7 Fibergla	ISS	SI	DR-26		T	hreaded		
Blank casing Diameter			to 20	ft.,	Dia	in.	to	ft., Dia	in.	to	ft.	
Casing height above las			in.,	w	eight 2.3		lbs. / ft.	Wall thickness		.21	.4	
TYPE OF SCREEN OF SCREEN OF STREET	IATERIAL:	5 Fiberglas	7 PVC 10 Asbestos-ce									
2 Brass 4 G	5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS				lother (specify)							
_		7 1105			8 Saw cut	2 None used (op						
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot				5 Gauzed wrapped 6 Wire wrapped			9 Drilled ho	Inc	11 None (o	en noie)		
2 Louvered shutter					10 Other (s							
SCREEN-PERFORAT	4 Key pu ION INTERV		from 20		7 Torch c ft. to			` '	• /		_	
from							ft., From		ft. to		ft.	
GRAVEL PACK INTERVALS: from 20			ft. to ft. to 32			ft., Fro ft., Fro		ft. to		ft.		
from			ft. to			ft., Fro		ft. to ft. to		ft. ft.		
6 GROUT MATERIA	L: 1 Neat o	cement	-	ement grout			tonite		ntonite h	ole pluo		
Grout Intervals: From ft. to ft. From 0 ft. to 20									-			
What is the nearest source of possible contamination:						10 Livestock pens		14 Abandon water well				
1 Septic tank 4 Lateral lines			7 Pit privy			11 Fuel storage		15 Oil well/Gas well				
2 Sewer lines 5 Cess pool			8 Sewage lagoon			12 Fertilizer storage 13 Insecticide storage		16 Other (specify below)				
3 Watertight sewer lines 6 Seepage pit				9 Feedyard 13 Insec			None Apparent					
Direction from well? FROM TO LITHOLOGIC LOG						FROM	то	How many	nany feet? PLUGGING INTERVALS			
	psoil	J. III OL	OGIC DOG			FROM		PLU	GGING INTER	YALS		
3 17 cl	ay			*** ***								
17 22 fi	ne sand											
22 32 gr	ey shale)										
							- -					
						7.0						
7 CONTRACTOR'S	OR LANDOWNE	R'S CEDTII	FICATION: Th	is water we	ll was (1)	construc	ted (2) recon-	structed or (2)	dunned under	my juriodic	tion and	
was completed on (r	mo/day/year)) .	1-16-200	2		and this i	record is true	to the best of m				
Water Well Contract	or's License				s Water	Well Reco	rd was compl	eted on	, s ougo (
(mo/dav/vr)1-21	-2002						•		~ · ·	011		
Under the business	name of	нагр	Well &	Pump Se	rvice,	Inc	by	(signature)	Todd	S. Har	DO I	