1 LOCATION OF WATER WELL:			FRACTION Center of W 1/2			Section Number	n Number Township Number		Range Number		
Harvey			Cer	Center of W/2			т 23		112		
Distance and direction frem nearest town or city street address of well if located within city?											
Sharps Drive and Meridian Newton, Kansas (5160rtica) Neconety)											
water well owner: NEWTON, City of											
RR#, ST. ADRESS, BOX#: P.O.BOX 687  Board of Agriculture, Division of Water Resource											
1	Y, STATE, ZI	·	Kansas								
				IPLETED WELL	35	ft. ELI	EVATION:	plication Number	: 20020000		
	" IN SECTION	N BOV.	Depth(s) groundw		1	ft.	2	ft.	3	£.	
1 +		<del> </del>	, .	ATER LEVEL 15			Z RFACE MEASURED O		3-27-2002	ft.	
f		WE	LL'S STATIC W Pump test					• •			
'	NW-	NE -	-			ft.	after	hours pump	•	gpm	
ا ≝	1	1 1 1	Yield	~	iter was	ft.	after	hours pum	oing	gpm	
M Mile	/ <del>X</del>	1 121	Hole Diameter	12 in. to		ft.	and	in.	to	ft.	
1		1 ' 1 1	LL WATER TO		Public wate		8 Air conditioning		jection well		
1	sw	SE	1 Domestic		Oil field wa		9 Dewatering	12 0	ther (Specify belove	w)	
	l		2 Irrigation	, -	•		10 Monitoring well -	_			
*	ـــنــــــــــــــــــــــــــــــــــ	e I		riological sample sub	mitted to I	•		_ · ·	o/day/yr sample w 	ras	
5 TYPE OF CASING USED: 5 Wrought iron 8 Congrete tile CASING IOINTS: Clied X Cleaned											
				5 Wrought iron		Concrete tile	CASING JO		ued X Clamped	i	
1 Stee		3 RMP (SR)		6 Asbestos-Cement		Other (Specify b	oelow)	Welded			
2 PV		4 ABS		7 Fiberglass	SI	DR-26		T	readed		
L	asing Diar		to 20	ft., Dia	in.	to	ft., Dia	in.	to ft.		
	O	ve land surface 12	in.,	weight 2.3		lbs. / ft.	Wall thickness or		.214		
!		EN OR PERFORATION	N MATERIAL:	5 Fiberglass		PVC		sbestos-ceme			
1 Ste		3 Stainless Steel		-		RMP (SR)		ther (specify)			
2 Bra		4 Galvanized steel		6 Concrete tile	y	ABS		one used (op	en hole)		
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped							8 Saw cut		11 None (open l	hole)	
	nous slot	3 Mill slot		6 Wire w	6 Wire wrapped			9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 20 ft. to 35 ft., From ft. to									ft.		
from				ft. to		ft., Fron	1	ft. to		ft.	
GRAVEL PACK INTERVALS: from 20				ft. to 35		ft., From		ft. to		ft.	
<b></b>			from	ft. to		ft., From		ft. to		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug											
ľ	ntervals:			ft. From	ft.	to	ft. From	0	ft. to 20	ft.	
What is the nearest source of possible contamination:				- Di.		10 Livestock pens		14 AI	oandon water well	ł	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel storage		15 Oil well/Gas well				
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage 13 Insecticide storage		16 Other (specify below)				
	rtight sew		it	9 Feedyard		15 Insecti	ciue storage	None Apparent			
	n from we		101 00101 00			· · · · · · · · · · · · · · · · · · ·	How many fee				
FROM 0	TO	topsoil	IOLOGIC LOG		FROM	ТО	PLUGO	GING INTER	VALS		
4	18	clay									
18	25	silty sand									
25	35	shale				-					
23	33	BHATE				-					
	<b></b>										
						-					
						-					
						-		#			
						-					
	·					-					
						.1					
7 CON	NTRACTO	OR'S or landowner's ci	ERTIFICATION: Thi								
was c	ompleted	on (mo/day/year)	3-27-200	<b>_</b>	. and this	record is true t	o the best of my	knowledge a	and belief. Kans	as	
Water	Well Cor	ntractor's License No.	430	This Water	Well Reco	ord was comple	ted on				
(mo/day/yr)3-29-2002 Under the business name of Harp Well & Pump Service, Inc											
under	me bust	ness name of	·			by (	signaturė)	Sødd	S. Tarp		