GSI Job No. 057285	WATER	MELL BECORD Farm W	0AIO 5 KOA 00- 4	040 ID No	Piezometer
1 LOCATION OF WATER WELL:		WELL RECORD Form V	Section Number	212 ID No Township Number	Range Number
	SE 1/4	SE % NE ;		T 23 S	R 01 E
Distance and direction from nearest to				1 23 5	K VI E
1701 S. Kansas St., N		33 of Well II located Within	Gity:		
2 WATER WELL OWNER:	Wal-Mart				
RR#, St. Address, Box # :	2001 SE 10 <sup>th</sup>	St		Board of Agriculture Dis	vision of Water Resources
City, State, ZIP Code :	Bentonville,			Application Number:	VISION OF WATER I LESCUIDES
LOCATE WELL'S LOCATON WIT					
AN "X" IN SECTION BOX:	DEPTH OF CO	MPLETED WELL	20 ft. ELE	/ATION:	
1	Depth(s) Groundwa	ter Encountered 1	ft.	. 2ft.	3 ft. On
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr					
,	Pump te	est data: Well water was	ff	t. after hours	pumping gpm
Wile W				t. after hours	pumping gpm M
7	Bore Hole Diameter	6.5 in. to	20	ft. and	n. to ft.
SWSE	WELL WATER TO	BE USED AS: 5 Public	water supply	ft. and  8 Air conditioning  9 Dewatering	1 1111000001111011
	1 Domestic	3 Feed lot 6 Oil fie	d water supply	9 Dewatering	12 Other (Specify below)
Y — — — — — — — — — — — — — — — — — — —	2 Irrigation	4 Industrial 7 Lawn	and garden (domesti	c) 10 Monitoring well	
S	Was a chemical/bad	cteriological sample subm	itted to Department?	Yes No X If yes	s, mo/day/yr sample was
	submitted			ter Well Disinfected? Yes	
5 TYPE OF BLANK CASING USED:		5 Wrought Iron 8			ed Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS	,	7 Fiberglass		Thre	aded Flush
Blank casing diameter <b>2</b> Casing height above land surface	in. to 10	ft., Dia	in. to	ft., Dia	in. to ft.
Casing height above land surface	Flushmount in.	, weight <b>0.7</b> 0	)3   ibs./ft.	Wall thickness or gauge No	Sch. 40
TYPE OF SCREEN OR PERFORATION	ON MATERIAL:		7 PVC	10 Asbestos-cem	ent
		5 Fiberglass	8 RMP (SR)	11 Other (specify 12 None used (or	·
		6 Concrete tile	9 ABS	12 None used (or	en hole)
SCREEN OR PERFORATION OPEN			rapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3	Mill slot	6 Wire wrap		9 Drilled holes	
2 Louvered shutter 4	Key punched	7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVAL	S: From 1	0 ft. to	<b>20</b> ft. F	rom ft.	toft.
	From	ft. to	ft. F	rom ft.	toft. 🗖
GRAVEL PACK INTERVALS	From 8	ft. to	<b>20</b> ft. F	rom ft.	to ft.
	From	ft. to	ft. F		to ft.
6 GROUT MATERIAL: 1 Nea	t cement 2 C	ement arout	3 Bentonite	4 Other	
Grout Intervals From 0.5	ft to 8	ft. From	ft to	ft From	ft to ft
What is the nearest source of possible	contamination:				pandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy			il well/ Gas well
2 Sewer lines		8 Sewage lage	on 12 Fertil	izer storage 16 O	ther (specify below)
3 Watertight sewer lines				ticide storage	(5,550,750,000)
Direction from well?  How many feet?					
	LITHOLOG	GIC LOG	FROM TO	PLUGGING	NTERVALS

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was 8-1-05 completed on (mo/day/yr) f. Kansas and this record is true to the best of my knowledge and bel

531 8-25-05 Water Well Contractor's License No. This Water Well Reco rd was completed on (mo/da) Geotechnical Services, Inc. under the business name of by (signature)

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

Shale, weathered, gray, very

Topsoil

Lean Clay

CH Fat Clay

soft

0.5

2.5

15

20

0

0.5

2.5

15

SEC