

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County HARVEY SE SE 1/4 NW 1/4 SE 1/4 Section Number 25 20 Township Number 1 23 S Range Number R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? 1007 S. Pine

2 WATER WELL OWNER: Jerry Rostetter RR#, St. Address, Box #: 1007 S. Pine City, State, ZIP Code: Newton, KS

Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S

4 DEPTH OF COMPLETED WELL 100 ft.

Depth(s) Groundwater Encountered (1) 18 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr. Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted. Water well disinfected? Yes X No

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below)

Blank casing diameter 5 in. to 100 ft. Diameter 16 in. to 100 ft. Diameter 100 in. to 26 ft. Diameter 100 in. to 26 ft. Casing height above land surface 16 in. weight 100 lbs./ft. Wall thickness or gauge No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 5 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 100 ft. From 24 ft. to 100 ft. GRAVEL PACK INTERVALS: From 24 ft. to 100 ft. From 25 ft. to 100 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 24 ft. to 25 ft. From 25 ft. to 25 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil wll/gas well

Direction from well? North How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 topsoil

2 23 clay

23 27 fine sand

27 41 green shale

41 100 blue shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/10/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 611 This Water Well Recored was completed on (mo/day/year) 10/3/05 Under the business name of Chase Drilling by (signature) fChase

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.