

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Harvey Fraction NW 1/4 NE 1/4 SW 1/4 Section Number 17' Township Number T 23 S Range Number R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? 201 W. Broadway, Newton, KS Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code KANSAS DEPARTMENT OF HEALTH AND ENVIRONMENT

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 23.58 ft. Depth(s) Groundwater Encountered (1) 8.53 ft. (2) ft. (3) ft. WELLS STATIC WATER LEVEL 8.53 ft. below land surface measured on mo/day/yr. 11/13/07 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELLS WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawns & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr Sample was submitted. Water well disinfected? Yes No X

5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped I Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded YES Blank casing diameter 2' in. to 8.58 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface -2 in., Weight SCH 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: I Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: I Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 23.58 ft. to 8.58 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 7.5 ft., From ft. to ft.

6 GROUT MATERIAL: I Neat cement 2 Cement grout 3 Bentonite 4 Other Cement Grout Intervals: From 7.5 ft. to 0.5 ft., From 0.5 ft. to 0 ft., From ft. to ft.

What is the nearest source of possible contamination: I Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well

Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0' 5 Clay, Brown-Yellow 5' 10 Clay, Green-Brown 10 15 Clay, Green-Grey 15 20 Clay, Green-Grey 20 25 Clay, Grey 25 Bedrock, shale, grey BCMW-2

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/5/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 665 This Water Well Record was completed on (mo/day/year) 12/5/07 under the business name of Pratt Well Service, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1 000 SW Jackson St., Suite 420, Topeka, Kansas 66612- 1 367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.