		WATER W	ELL RECO	RD Fo	orm WW	C-5 K	SA 82a-121	2			
1 LOCATION OF WA	TER WELL:	FRACTION	SE SE	NE		ION NUMBER		PNUMBER		GE NUME	3ER
Harvey		S/B/ 1/4	890 1/4		1/4	31	T 2	<u>3</u> S	R	1E	E/W
	iderson, 1/2 m	city street address of well		ewton, Ka	nese	(4 logs	on 1 permi	it)			
2 WATER WELL		WTON, CITY		ewton, ixe	111343	(4 logs	on I permi				
RR#,ST. ADDRE		O. Box 687						Board of Agri	iculture, Divisio	n of Wate	r Resource
CIT	Y, STATE: Ne	wton, Kansas			ZII	P CODE: 6	7114	Application Nur	mber: 2	200801	94
3 LOCATE WELL'S	LOCATION	4 DEPTH OF COME	PLETED WELL:	40	ft.		ELEVATION:				
WITH AN "X" IN S	I ECTION BOX:	Depth of groundwate	r Encountered:		ft.			ft.			ft.
		WELL'S STATIC WA	ATER LEVEL	10	FT. BELO	W LAND SU	JRFACE MEAS	JRED ON mo/o	day/yr:	5/16/0	8
,им	••••••NE		imp test data:	Well water			ft. after	hours	s of pumping	@	gpm
w ×		Est. Yield: Bore Hole Diameter	gpm r 12	Well water		0 ft	ft. after		s of pumping	_	gpm
- "		WELL WATER TO B	•	и.	to 4	O ft	. and	in.		to . Injectio	ft.
sw	SE			. Public wat	er supply	7. Lawn a	and garden onl	9. Dewateri	9	-	cify below)
		_		. Oil field wa		8. Air co	nditioning	10. Monitori	ng weli		
	s	Was a chemical/bacte submitted	eriological sample	submitted to De	epartment?	YES	NO Nater Well Disin	-	what mo/day	yyr was NO	•
5 TYPE OF C	ASING USED:				0.01			SING JOINTS:	Glued		hreaded
1. Steel	3. RPM	(SR) 5. Wrought	t Iron 7.	Fiberglass		ther (Specify	(below) CA	SING JOIN 13.	Welded		lamped
2. PVC	A. ABS	6. Asbesto	s-Cemerit 8.	. Concrete tile	e SDI	R-26				J	
Blank casing diam	eter 8	in. to	20 ft.,	Dia.	in.	to	ft.,	Dia.	in. to)	ft.
Casing height about	ove land surface:	12 in.,	'	<i>N</i> eight:	5.52 It	os. / ft.	Wall th	nickness or gaug	ge No.	332	
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous s			Gauzed wrapp	ed	7 To	rch cut	9 Dril	led holes	11. No	ne (one	n hole)
2. Louvered shu			Wire wrapped	-		w cut		er (specify)		ic (opc	ii iioic,
	•	, , , , , , , , , , , , , , , , , , , ,	• • • • • • • • • • • • • • • • • • • •					ei (specily)			
SCREEN - PERFO	RATION INTERVA		20 ft.	to	40	ft.,	From	ft.	to)	ft.
		From	ft.	to	40	ft.,	From	ft.	to)	ft.
GRAVEL	PACK INTERVALS		24 ft.	to	40	ft.,	From	ft.	to)	ft.
		From	ft.	to		ft.,	From	ft.	to		ft.
GROUT MATE	1.140	eat cement 0 ft. to	2. Cement 20 ft			B. Bentonite			tonite hole		
Grout Intervals What is the neares		e contamination:	,	From	ft.	to	ft.,	From	ft.	to	ft.
1. Septic tank	4. Late	eral lines 7	7 Di4			k pens	13. Insect	15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storag						rage	14. Abandon water well 16. Other (specify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1						r storage		None Apparent			
Direction from we	l?	LITUOLOGI	C10C		From	I T.	How m	any feet?	2010 1 0		
From To	tongoil	LITHOLOGI	C LUG		From	То		LITHOLO	OGIC LO	<u>خ</u>	
3 7	topsoil clay					-					
7 12	sandy soil										
12 27	fine sand										
27 40	gray shale										
		ertification: This water	`			constructe		plugged	under my ju	rsdiction	1 and
was completed	on (mo/day/year)	5-16-2008				-	knowledge and				
Kansas Water V	Vell Contractor's Lic	cense No. 236	1	his water we	ell record wa	as complete	d on (mo/day/ye	ar) 5-19	9-2008		
under the busin	ess name of Hai	rp Well and Pu	mp Service	i	by (si	gnature)	T	odd S	S. Ha	v b	