		WATER W	ELL RECO	ORD F	orm WV	VC-5 K	SA 82a-12	12		
1 LOCATION OF WAT	ER WELL:	FRACTION				TION NUMBE	1	P NUMBER	RANGE N	
Harvey		SE 1/4			1/4	27	Т 2	3 S	R 11	C E/W
Distance and direction from nearest town or city street address of well if located within city? 1/2 m. East of Spencer Rd., So. side of SE 12th Newton, Kansas (10 logs on 1 permit)										
2 WATER WELL OWNER: NEWTON, CITY OF										
RR#,ST. ADDRESS		E. 6th	.					Board of Agri	culture, Division of V	Vater Resource
1		wton, Kansas			ZI	P CODE:		Application Num	nber: 2010	00273
3 LOCATE WELL'S L	OCATION 4	DEPTH OF COM	PLETED WELL	.: 35	ft.		ELEVATION:			*****
WITH AN "X" IN SE		ם epth of groundwat∈	er Encountered:		ft.			ft.		ft.
		VELL'S STATIC W	ATER LEVEL	15	FT. BELO	W LAND SU	JRFACE MEAS	URED ON mo/d	lay/yr: 7/22	2/10
NW X	NE	Pu	ımp test data:	Well water	er was		ft. after	hours	of pumping @	gpm
W Wile	1	Est. Yield:	gpm	Well wat	er was		ft. after	hours	of pumping @	gpm
∑ w	'	Bore Hole Diamete		in.	to 3	55 ft.	and	in.	to	ft.
sw		VELL WATER TO I		Dublic wat	er eunnly	7 lawn:	and garden only	9. Dewateri	المنافقة المنافقة	ction well
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample										
		submitted			····	Was \	Water Well Disin	fected? (YES	NO
5 TYPE OF CA		5. Wrough	t Iron 7	. Fiberglass	9. Ot	ther (Specify	/ below) CAS	SING JOINTS:	Glued	Threaded
1. Steel 3. RPM (SR) Welded Clamped										
2. PVC Blank casing diamet	> 4. ABS er 5	in. to	20 ft.,	Dia.	in.	••	ft.,	Dia,		4
	_	10				to	,		in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slo			Gauzed wrapp	ed	7. T o	rch cut	9. Dril	led holes	11. None (c	open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)										
		•						or (opcony,		
SCREEN - PERFOR	ATION INTERVAL		20 ft.	to .	35	ft.,	From	ft.	to	ft.
00.005	01/11/2007	From	ft.	to	25	ft.,	From	ft.	to	ft.
GRAVEL PA	ACK INTERVALS:	From	20 ft.	to	35	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug										ug
Grout Intervals: What is the nearest s	From 0		20 ft.,	From	ft.	to	ft.,	From	ft. to	ft.
1. Septic tank	4. Later		7. Pit privy	10	D. Livestoc	k pens	13. Insect	icide storage	15. Oil well/0	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below										ecify below)
3. Watertight sew			Feed yard	1:	2. Fertilizeı	rstorage			None Ap	parent
Direction from well?							How m	How many feet?		
From To		LITHOLOGI	C LOG		From	То		LITHOLO	GIC LOG	
0 3	topsoil									
3 15	clay									
15 30 30 35	fine sand grey shale									
310 31.3	grey silate									
ļ	-									
	 									
	1								4 · 4 ·	·
	-									
								 	 	
7 Contractor's or	landa	Marking Th					1 05 0	mlummad	and ne mar trade at the	tion and
F/20/2010										
was completed on	(mo/day/year)	7/22/2010	and	this record is	s true to the	best of my	knowledge and	belief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/26/2010										
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourb										