WATER WELL REC	CORD	Form W	WC-5	Division of Wate	er Resources App. No	,. L		
		Fraction	1	Section Number	Township No.	Range N		
County: Harrey		Nw4 Nw4>	1 W/4 NW 1/4 > W/4 1/4			R	<b>X</b> E □W	
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning				
from nearest town or intersection: If at owner's address, check here .				Latitude: (in decimal degrees)				
do le Maria				Longitude: (in decimal degrees) Elevation:				
3E pn 12 58. 2 N Newton				D 7770004				
2 WATER WELL OWNER: Graber Backhoe RR#, Street Address, Box #: 10116 NW 16034				Collection Method:				
RR#, Street Address, Box #: 101/6 NW 160 EL				GPS unit (Make/Model:)				
City, State, ZIP Code	Digital Map/Pr	noto, Topographic						
3 LOCATE WELL	IVGW (	ton, Ks 6	11100	Est. Accuracy:	<3 m, □ 3-5 m, □	5-15 m, <u>Г</u>	] >13 m	
WITH AN "X" IN		COMPLETED WEI		ft.				
SECTION BOX:	Depth(s) Groundwater Encountered (1)3. 5 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr. 7							
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yrft.								
Pump test data: Well water wasft. after hours pumping								
W NW NE E EST. YIELD Oppn Well water was							gpm	
W   E   Bore Hole Diameter								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well  Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Colored   Colo								
	Was a chemical/bacteriological sample submitted to Department?  Yes  No							
S If yes, mo/day/yr sample was submitted								
mile		fected? 🕱 Yes 🔲						
5 TYPE OF CASING U	SED:	<b>₩</b> PVC □	Other	110-200				
CASING JOINTS: N Glued Clamped Welded Threaded								
Casing diameter								
Casing diameter in. to								
TYPE OF SCREEN OR PERFORATION MAŢERIAL:								
Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 3.0 ft. to 5.0 ft., From 76 ft. to 6.1								
SCREEN-PERFORATED INTERVALS: From 3.2 ft. to 5.0 ft., From ft., From ft. to ft.								
From ft to ft From ft to ft								
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From C. ft. to 2.0 ft., From ft. to ft.								
What is the nearest source of possible contamination:								
Septic tank    Lateral lines    Pit privy    Livestock pens    Insecticide storage    Other (specify below)								
Sewer lines	Cesspool	Sewage lagoon	☐ Fuel storage	Abandoned	i water well	(-1)	,	
Watertight sewer li	C.		Fertilizer st		is well			
Direction from well		707.00		from well				
FROM TO	LITHOLOG		FROM	TO LITHO. LO	OG (cont.) or PLUC	JGING II	NTERVALS	
0 00 104	Soil	Brow Cla	<del></del>					
00 10 6-	0 Ban	1						
22 30 411	0 34M	<u> </u>						
30 48 fin	etom	ed Band						
	200.11	co sand						
4299 Blu	OLGr	av Shal						
7000		7						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was □ constructed, □ reconstructed, or □ plugged								
under my jurisdiction and was completed on (mo/day/year)								
						5-10	3-10	
under the business name of	t Pack!	118 Urilli	16	by (signature)	TRAIL	ank	ua	
INSTRUCTIONS: Use typewing (white, blue, pink) to Kansas I								
Telephone 785-296-5522 Sen								