WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
County: Harvey	Sw 1/4/10 1/4Sw1	4 21 T 23 S R / ZE W
Street/Rural Address of Well Location	n; if unknown, distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection: If	at owner's address, check here 🔼	Latitude: (in decimal degrees)
		Longitude: (in decimal degrees)
		Elevation:
2 WATER WELL OWNER: De/	la Rostan	Datum: WGS 84, NAD 83, NAD 27
2 WATER WELL OWNER: Della RR#, Street Address, Box #: City, State, ZIP Code	2 Of Consolin 1) and	Collection Method: GPS unit (Make/Model:)
City, State, ZIP Code :	Sherman Dr.	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
IVe	Uton, Ko 67/14	Est. Accuracy:
3 LOCATE WELL		Pro
WITH AN "X" IN 4 DEPTH O	F COMPLETED WELL	9 ft.
SECTION BOX: Depth(s) Gro	undwater Encountered (1)d.	ft. (2)ft. (3)ft.
WELL STATIC WATER LEVEL		
Pu Pu	mp test data: Well water was	ft. after hours pumping gpm
EST. YIELD 13. gpm, Well water was ft. after hours pumping gpm Bore Hole Diameter in. to 20. ft., and 7.2 in. to 3. ft.		
W E Bore Hole Diameter		
	ER TO BE USED AS: Public w	ater supply Geomermal Injection well
□ Domestic □ Feedlot □ Oil field water supply □ Dewatering □ Other (Specify below) □ Irrigation □ Industrial □ Domestic-lawn & garden □ Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No		
S If yes, mo/day/yr sample was submitted		
Water well disinfected? Yes No		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: The Charlest Commod Co		
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight DR 24 lbs./ft., Wall thickness or gauge No. 24 ft.		
Casing diameter		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
Steel Stainless Steel PVC Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to 22 ft., From ft. to		
SCREEN-PERFORATED INTERVALS: From		
From		
From		
6 GROUT MATERIAL: Neat cement Coment grout Bentonite Other		
Grout Intervals: From		
What is the nearest source of possible contamination:		
manna nama	lines Pit privy Livestock	c pens
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well		
Watertight sewer lines Seepa	ge pit Feedyard Fertilizer	
Direction from well		e from well . \$\frac{43}{3}.
	OGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
O 10 Clay		
To 19 Sand		
10 11- 121 0	- 6)	
19 15 Blue & Gx	ray shale	
N 100 C 1 C 1 1	/ 6/ / / / -	
15 10 Crum bled	Shale & Water	
01 00 0		
76 G3 Cray Sha	10	
7 CONTED A CTODES ON Y ANTIQUEIN	ENERGY CHRESTOPHENE A TOTAL COST.	to will use of a set of a first o
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Zeonstructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year)		
under my jurisdiction and was completed on (mo/day/year)		
under the business name of John A. J.		
under the business name of		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212		