WATER WELL RECORD	Form W	WC-5		r Resources App. N	o	
1 LOCATION OF WATER WE	LL: Fraction 4/Ve 1/4/Ve	2 1/4 5 14	Section Number	Township No. T 23 S	Range Number R	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:						
from nearest town or intersection: If at owner's address, check here Latitude:						
	Longitude: (in decimal degrees)					
			Elevation:			
2 WATER WELL OWNER: 1	12/2/1/10/20	Lan	Datum: WGS 84	1, ∐ NAD 83, ∐] NAD 27	
2 WATER WELL OWNER: Bob Winchester RR#, Street Address, Box #: Description Address Address			Collection Method: GPS unit (Make/Model:)			
C'AL STATE OF THE COLOR OF THE			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Λ	lewton, Kg	01/14	Est. Accuracy: <			
3 LOCATE WELL	/		2			
WITH AN "X" IN 4 DEPT	TH OF COMPLETED WELL		ft.	A /	(2)	
SECTION BOX: Depth(s)	Depth(s) Groundwater Encountered (1)					
WELL S	Pump test data: Well water was					
EST YII	EST VIELD 4 5 gare, Well water was ft after hours numping gam					
w NW NE E Bore Hol	Bore Hole Diameter					
	WELL WATER TO BE LIGED AS. Deblic mater comply Coethornal Dirication well					
SW SE	SW SF Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
Irrigation Industrial Momestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No						
S If yes, mo/day/yr sample was submitted						
Water we	ell disinfected? Yes					
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight S.D.R.26.lbs./ft., Wall thickness or gauge No. 21.4						
Casing height above land surfacein., Weight D. D. B. L. B. L. B. Wall thickness or gauge No						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torcheut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Screen-Perforated intervals: From Ho. ft. to 70 ft., From 15 ft. to 90 ft.						
SCREEN-PERFORATED INTERVALS: From						
From						
GRAVEL PACK INTERVALS: From						
6 CDOUT MATERIAL. Next coment Coment grout Provide Other						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
What is the nearest source of possible contamination:						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewar lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well						
Direction from well	TOT OCIOL OC					
	HOLOGIC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	JGGING INTERVALS	
0 15 Xellow	Clay	 				
15 66 31.00	1 - 10	 			10001	
15 63 BIVES	n & G					
63 64 CTUMB	led Shale & 1	Waste	n		4.47.47	
US WI CIOMB	ies share c	1000				
64 90 Blue 1	Gray Shale					
VI TO CIVE -	sing since				And	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/dey/year)						
Kansas Water Well Contractor's License No						
under the business name of						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRWT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy	to WATER WELL OWNER and	retain one for you	ur records. Include fee	of \$5.00 for each	constructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212						