WATER WELL RECORD	Form W	WC-5	Di	vision of Wate	r Resources App. No	_{),}		
1 LOCATION OF WATER WELL: County: Harvey	Fraction 4Se 4Ne	14Ne4	Section	on Number	Township No.	Range N	lumber	
Street/Rural Address of Well Location; i					System (GPS) in	formation:		
from nearest town or intersection: If at o				_				
			_			(in dec	imal degrees)	
						••••		
2 WATER WELL OWNER: MOL	SC4 \ da L	<u></u>			4, 🗌 NAD 83, 🔲	NAD 27		
2 WATER WELL OWNER: MeliSSA Webb RR#, Street Address, Box #: // PRobtail				Collection Method: GPS unit (Make/Model:)				
City State ZID Code				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
Newton, Kg 6/1/4 Est. Accuracy: State, 21P Code : Newton, Kg 6/1/4 Est. Accuracy: State, 21P Cod								
3 LUCATE WELL	•	<i>[]</i>	2	_				
with an "x" in 4 DEPTH OF (COMPLETED WELL	L	ن	ft.				
SECTION BOX: Depth(s) Ground	SECTION BOX: Depth(s) Groundwater Encountered (1)							
WELL'S STATIC WATER LEVEL								
Pump	test data: Well wate	r was ڪ. ۾	π (Δ	. aner	nours pump	oing	gpm	
W NW NE EST. YIELD. St. 7. gppa. Well water was								
W E Bore Hole Diameter								
Domestic Deadlot Doil field water supply Dewatering Dother (Specify below)								
SW SE								
Was a chemical/bacteriological sample submitted to Department? Yes								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 5 in to 90, ft., Diameter ft., Diameter ft., Diameter ft., Diameter ft.								
Casing diameter 5 in to 70 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface in., Weight 5.00 Wall thickness or gauge No. 2 ft.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat ceme	nt Cement grout	Bento	nite [Other	•			
		1	ft. to	ft.,	From	. ft. to	ft.	
What is the nearest source of possible conta		T investe els		☐ T-cookisida	otamon D Oth	an (ann acife	halam)	
Septic tank ☐ Lateral lin ☐ Sewer-lines ☐ Cesspool		☐ Livestock☐ Fuel stora		☐ Insecticide ☐ Abandoned		er (specify	below)	
Watertight sewer lines Seepage p		Fertilizer		Oil well/ga				
Direction from well					- • • • • • • • • • • • • • • • • • • •			
FROM TO LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) <u>or</u> PLU	GGING I	NTERVALS	
0 5 Clay								
30 & Sandy Clay	7							
B 15 YEllow Cla	/							
	·				<u> </u>			
15 74 Blue Shalo		ļ						
A	1		, ,					
14 1/5 Crumbled	smer S	mel	NWI	er_				
775 04 571 0	. 04 1-	 		<u> </u>				
	y Shale	NT. PETI-	11			4_ 1	TI1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year)								
under the business name of					aul Do			
INSTRUCTIONS: Use typewriter or ball point pen	. PLEASE PRESS FIRM	and PRINT c	early. Ple	ase fill in blank	s and check the correc	t answers.	Send three conies	
(white, blue, pink) to Kansas Department of Health	and Environment, Bureau	of Water, Geo	logy Section	on, 1000 SW Ja	ckson St., Suite 420,	Topeka, Kau	nsas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdbake.gov/waterwell/index.html								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212								