## KOLAR Document ID: 1455668

	WELL R		-	WWC-5			vision of Wat						
		Correction		e in Well Use			ources App.		[]	Well ID			
<b>1 LOCATION OF WATER WELL:</b> Fraction							ction Numb	er	Township Numb		ige Number		
County: 1/4 1/4 1/4						1⁄4							
							treet or Rural Address where well is located (if unknown, distance and						
Business: Address:				rection from nearest town or intersection): If at owner's address, check here:									
Address: Address:													
City:			State:	ZIP:									
<b>3 LOCATE WELL</b> WITH (52) IN <b>4 DEPTH OF COMPLETED WELL:</b>													
SECTIO	<b>SECTION BOX:</b> N $2) \dots \dots ft. 3) \dots ft. or 4) \square$												
1	N WELL'S STATIC WATER LEVEL:										AD 27		
			below land surface, measured on (mo-day-yr)					Source for Latitude/Longitude:					
NW	NF		above land surface, measured on (mo-day-yr)					(WAAS enabled? $\Box$ Yes $\Box$ No)					
			t data: Well water was ft.					□ Land Survey □ Topographic Map			(0)		
w				irs pumping gpm				Online Mapper:					
SW					ater was ft.								
	anter				s pumping gpm			6 Elevation:ft.  Ground Level  TOC					
			Tield:gpm Diameter: in. to ft. and			6 J		Source:  Land Survey  GPS  Topographic Map					
S Bore Hole Diame							boun						
Imile													
1. Domestic:       5. Dublic Water Supply: well ID       10. Oil Field Water Supply: lease													
	□ Household												
				echarge: well ID		□ Cased □ Uncased □ Geotechnical							
	Livestock 8. Monitoring: well ID							12. Geothermal: how many bores?					
2. 🗌 Irrigati	2. Irrigation 9. Environmental Remediation: well ID.						a) Closed Loop 🔲 Horizontal 🗌 Vertical						
	3. 🗌 Feedlot 🗌 Air Sparge 🗌 Soil Vapor E							b) Open Loop 🗌 Surface Discharge 🔲 Inj. of Water					
4. Industrial Recovery Injection									13. 🗌 Other (specify):				
Was a chemical/bacteriological sample submitted to KDHE?  Yes No If yes, date sample was submitted:													
Water well disinfected?  Yes No													
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded													
Casing diameter in. to ft., Diameter in. to ft., Diameter ft.													
Casing height above land surface													
TYPE OF SCREEN OR PERFORATION MATERIAL:													
Steel     PVC     Other (Specify)													
Brass       Galvanized Steel       None used (open hole)         SCREEN OR PERFORATION OPENINGS ARE:       Image: Comparison of the sector of													
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)													
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)													
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft. to ft.													
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft. o ft. o ft. o ft. o ft. to ft. ft. ft. ft. ft. ft. ft. ft. ft.													
				ft., From	ft.	to	ft., Fron						
		e contaminati	on: No	potential source of c	ontar	nination wi	thin 200 ft.						
Septic			Lateral Line				Livestock P			cide Storage			
			Cess Pool				Fuel Storag			oned Water	Well		
	ight Sewer Lin			☐ Feedyard			Fertilizer St	torage	e 🗌 Oil We	ll/Gas Well			
Direction from well? ft.													
10 FROM	TO		ITHOLO		wen	FROM	ТО		THO. LOG (cont.) or		GINTERVALS		
10 11(0101	10	L			-+	1 1000	10			120000			
					-+								
								1					
								1					
								1					
								1					
						Notes:	1						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged													
under my jurisdiction and was completed on (mo-day-year) and this record is true to the best of my knowledge and belief.													
Kansas Water Well Contractor's License No													
under the business name of													
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.													
-		ks gov/waterwel			1000	ST JUCKSUI	. <i>5</i> ., <i>5</i> unc <del>7</del> 20	., 10p	, 1x11505 00012-130		SA 82a-1212		