WATER WELL R			ion of Water		
The state of the s	Correction		rces App. No.	Well ID	
1 LOCATION OF W	ATER WELL: Fraction	Section	on Number	Township Number Range Number	
County: WOOdSON NW 45E 4 NW 4 W 4 Z6 Z3T S REDE W					
2 WELL OWNER: Last Name: 1000 Stow First: WeS Street or Rural Address where well is located (it unknown, distance and					
Address: 17 We	st Gangay St	direction from ne	rom 200 and Source 20, 1 mile North		
Address:					
city: Leroy	State: W. 3 ZIP:66 857	14 mi eg	ist in s	pasture	
3 LOCATE WELL	4 DEPTH OF COMPLETED WELL	.65 A	5 Lottende	e: 38.01923 (decimal degrees)	
WITH "X" IN	Depth(s) Groundwater Encountered: 1)3	7	Lautuu	de: -95:6.2.29.5(decimal degrees)	
SECTION BOX:	2) ft. 3) ft., or 4		Horizont	al Datum: WWGS 84 D NAD 83 D NAD 27	
N	WELL'S STATIC WATER LEVEL: 75.	ft.	Source for Latitude/Longitude:		
	below land surface, measured on (mo-day-yr)		GPS (unit make/model:)		
NE	above land surface, measured on (mo-day-yr)		(WAAS enabled? Yes No)		
	Pump test data: Well water was		☐ Land Survey ☐ Topographic Map		
W	after hours pumping		L) Onli	ne Mapper:	
SW SE	afterhours pumping				
	l m			n:ft. Ground Level TOC	
S	Bore Hole Diameter: in. to	5.7. ft. and		☐ Land Survey ☐ GPS ☐ Topographic Map	
mile	in. to	ft.	<u> </u>	Other	
7 WELL WATER TO					
1. Domestic:	5. Public Water Supply: well ID		10. ☐ Oil F	field Water Supply: lease	
☐ Household ☐ Lawn & Garden	6. ☐ Dewatering: how many wells?7. ☐ Aquifer Recharge: well ID		II. lest no	le: well ID	
Livestock	8. Monitoring: well ID			mal: how many bores?	
2. Irrigation	9. Environmental Remediation: well			ed Loop Horizontal Vertical	
3. Feedlot	☐ Air Sparge ☐ Soil Vapo	r Extraction	b) Oper	Loop Surface Discharge Inj. of Water	
4. Industrial	☐ Recovery ☐ Injection		13. 🗌 Othe	r (specify):	
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:					
Water well disinfected?	✓ Yes □ No			-	
8 TYPE OF CASING	USED: Steel PVC Other	CASIN	G JOINTS:	Glued Clamped Welded Threaded	
8 TYPE OF CASING USED: Steel PVC Other					
Casing height above land surfacein. Weight					
Casing height above land	surface in. Weight	ios./π.	Wall thickne	as or gauge No. Soll 26	
Casing height above land	surface		Wall thickne		
TYPE OF SCREEN OF	surface	:	Wall thickne	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stain Stain Brass Galv	R PERFORATION MATERIAL: calless Steel		Wall thickne		
Casing height above land of TYPE OF SCREEN OF Stain Steel Stain Galv SCREEN OR PERFOR Continuous Slot	surface	e used (open hole)	Wall thickne	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stain Screen Galvace Screen OR PERFOR Continuous Slot Louvered Shutter	surface	e used (open hole) Torch Cut	Wall thickne	☐ (Specify)	
Casing height above land of TYPE OF SCREEN OF Stain Screen OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI	in, Weight PERFORATION MATERIAL: calcas Steel	e used (open hole) Torch Cut	Wall thickned Other illed Holes income (Open Holes 5	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stair Screen OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATION GRAVEL PAGE	in, Weight PERFORATION MATERIAL: cless Steel Fiberglass PVC Panized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped ED INTERVALS: From	e used (open hole) Torch Cut Dr Saw Cut No ft., From ft., From	Wall thickned Other illed Holes [one (Open Hole 5	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stain Screen OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE OF GROUT MATERIA	in. Weight PERFORATION MATERIAL: concludes Steel Fiberglass PVC conized Steel Concrete tile Non ATION OPENINGS ARE; Mill Slot Gauze Wrapped ED INTERVALS: From	Torch Cut Dr Saw Cut No ft., From Bentonite Do	Wall thickned Other illed Holes [one (Open Hole fi. to	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stair Screen OF PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE OF GROUT MATERIA Grout Intervals: From 2	in, Weight PERFORATION MATERIAL: cless Steel Fiberglass PVC Panized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped ED INTERVALS: From Fit to CK INTERVALS: From Fit to CK Punched CE CE CE CE CE CE CE C	Torch Cut Dr Saw Cut No ft., From Bentonite Do	Wall thickned Other illed Holes [one (Open Hole fi. to	(Specify)	
Casing height above land TYPE OF SCREEN OF Stair Steel Stair Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From Continuous Slot GRAVEL PAGE GROUT MATERIA Grout Intervals: From Continuous Slot GRAVEL PAGE GRAVEL P	in. Weight PERFORATION MATERIAL: concerned in the property of	Torch Cut Dr Saw Cut No ft., From Bentonite Ot	Wall thicknes Other Other illed Holes [one (Open Hole f. to	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stair Screen OF PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE OF GROUT MATERIA Grout Intervals: From 2	in. Weight PERFORATION MATERIAL: nless Steel	Torch Cut Dr Saw Cut No ft., From Bentonite Do ft. to	Wall thickned Other illed Holes [one (Open Hole fi. to	(Specify)	
Casing height above land of TYPE OF SCREEN OF Stain Steel Stain Galve SCREEN OR PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From Court Interva	in. Weight PERFORATION MATERIAL: canized Steel	Torch Cut Dr Saw Cut No. ft., From Bentonite Oth	Wall thickned Other Other One (Open Hole Market In to Other It, From Livestock Pens	(Specify)	
Casing height above land of TYPE OF SCREEN OF Steel Stain Galve Screen OF PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: calcass Steel	Torch Cut Dr Saw Cut No ft., From Bentonite Ot ft. to	Other Other Other illed Holes [one (Open Hole fi. to ft. to ther ther Livestock Pens Fuel Storage Fertilizer Stora	Other (Specify)	
Casing height above land of TYPE OF SCREEN OF Stain Steel Stain Galve SCREEN OR PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From Court Interva	in. Weight PERFORATION MATERIAL: canized Steel	Torch Cut Dr Saw Cut No. ft., From Bentonite Ot It to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From Court Intervals:	in. Weight PERFORATION MATERIAL: nless Steel	Torch Cut Dr Saw Cut No ft., From Bentonite Ot ft. to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From Court Intervals:	in. Weight PERFORATION MATERIAL: nless Steel	Torch Cut Dr Saw Cut No. ft., From Bentonite Ot It to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well?	in. Weight PERFORATION MATERIAL: nless Steel	Torch Cut Dr Saw Cut No. ft., From Bentonite Ot It to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: nless Steel	Torch Cut Dr Saw Cut No. ft., From Bentonite Ot It to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: aless Steel Fiberglass PVC ranized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped Rey Punched Pit Privy Rey Punched Pit Privy Rey Punched	Torch Cut Dr Saw Cut No. ft., From Bentonite Ot It to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: nless Steel	Torch Cut Dr Saw Cut No. ft., From Bentonite Ot It to	Wall thickned Other Other One (Open Hole Market In to	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: aless Steel Fiberglass PVC ranized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped Rey Punched Pit Privy Rey Punched Pit Privy Rey Punched	Torch Cut Dr Saw Cut No	Wall thicknes Other Other illed Holes [one (Open Hole 5	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: aless Steel Fiberglass PVC ranized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped Rey Punched Pit Privy Rey Punched Pit Privy Rey Punched	Torch Cut	Wall thickned will be the content of	Other (Specify)	
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE GROUT MATERIA Grout Intervals: From 2 Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: aless Steel Fiberglass PVC ranized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped Rey Punched Pit Privy Rey Punched Pit Privy Rey Punched	Torch Cut	Wall thickned will be the content of	Other (Specify)	
Casing height above land TYPE OF SCREEN OF SCREEN OF Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAGE OF GROUT MATERIA Grout Intervals: From ZNearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify)	in. Weight PERFORATION MATERIAL: aless Steel Fiberglass PVC panized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped Punched Wire Wrapped Rey Punched Rey Punched Rey Punched Wire Wrapped Rey Punched R	e used (open hole) Torch Cut	Wall thickned will be the control of	(Specify) Other (Specify) e) ##2. ft., From	
Casing height above land TYPE OF SCREEN OF SCREEN OF SCREEN OF SCREEN OF PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE OF GROUT MATERIA Grout Intervals: From Z Nearest source of possible Sewer Lines Watertight Sewer Lines Other (Specify) Control from well? 10 FROM TO 3 3 35 25 37 31 47 41 CONTRACTOR'S under my jurisdiction as	in. Weight PERFORATION MATERIAL: aless Steel Fiberglass PVC panized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Rey Punched Wire Wrapped Punched Wire Wrapped Rey Punched Rey	e used (open hole) Torch Cut	Wall thickned will be the control of	(Specify) Other (Specify) e) #2. ft., From	
Casing height above land TYPE OF SCREEN OF SCREEN OF SCREEN OF SCREEN OF SCREEN OF PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE OF GROUT MATERIA Grout Intervals: From Z Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Cother (Specify) Direction from well? 10 FROM TO 3 3 55 25 3 1 31 47 41 CONTRACTOR'S under my jurisdiction as Kansas Water Well Cother (Specify)	in. Weight PERFORATION MATERIAL: alless Steel Fiberglass PVC ranized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Key Punched Wire Wrapped ED INTERVALS: From	e used (open hole) Torch Cut	Wall thickned Other filled Holes [one (Open Hole filled Ho	(Specify) Other (Specify) e) #2. ft., From	
Casing height above land TYPE OF SCREEN OF Stain Brass	in. Weight PERFORATION MATERIAL: alless Steel Fiberglass PVC anized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Key Punched Wire Wrapped ED INTERVALS: From S. ft. to .6. CK INTERVALS: From Coment grout It to .3	e used (open hole) Torch Cut	Other illed Holes [one (Open Holes for the to ft. to ft. from ivestock Pens iv	(Specify) Other (Specify) e) #5. ft., From	
Casing height above land TYPE OF SCREEN OF SCREEN OF SCREEN OF SCREEN OF SCREEN OF PERFOR COntinuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE OF GROUT MATERIA Groat Intervals: From Z Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Cother (Specify) Direction from well? 10 FROM TO 3 15 25 3-1 31 47 41 CONTRACTOR'S under my jurisdiction at Kansas Water Well Counder the business nam Mail 1 white copy ale	in. Weight PERFORATION MATERIAL: alless Steel Fiberglass PVC ranized Steel Concrete tile Non ATION OPENINGS ARE: Mill Slot Gauze Wrapped Key Punched Wire Wrapped ED INTERVALS: From	e used (open hole) Torch Cut	Wall thicknes Other illed Holes [one (Open Holes for the to ft. to ft. to ilvestock Pens il	(Specify) Other (Specify) e) 4.5. ft., From ft. to ft. ft. ft. o ft. Insecticide Storage Abandoned Water Well ge Oil Well/Gas Well ft. ITHO. LOG (cont.) or PLUGGING INTERVALS Constructed, I reconstructed, or plugged true to the best of my knowledge and belief. Detail on (mo-day-year) 12-16-27	