

#1

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: HARVEY	SE 1/4 NW 1/4 SE 1/4	17	T 23 S	R 1E EW

Distance and direction from nearest town or city street address of well if located within city?

301 N MAIN NEWTON

2 WATER WELL OWNER:	OLD MILL PLAZA
---------------------	-----------------------

RR#, St. Address, Box # **LIDYPT. SMITH 301 N-HAIN ST- NEWTON KS 67114**

Board of Agriculture, Division of Water Resources

City, State, ZIP Code

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 16.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 11.2 ft. 2. 11.7 ft. 3. — ft.
	WELL'S STATIC WATER LEVEL 7.72 ft. below land surface measured on mo/day/yr 08-22-94
	Pump test data: Well water was — ft. after — hours pumping — gpm
	Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm
	Bore Hole Diameter: 8.625 in. to 16.5 ft. and — in. to — ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —	
Water Well Disinfected? Yes — No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded —
Blank casing diameter: 2 in. to 6 in. Dia — in. to — in. Dia — in. to — in. Dia — in. to — in.			Threaded X
Casing height above land surface: 0 in. weight SC440 lbs./ft. Wall thickness or gauge No. —			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 6 ft. to 16 ft. From — ft. to — ft. From — ft. to — ft. From — ft. to — ft.			
SAND GRAVEL PACK INTERVALS: From 5 ft. to 16.5 ft. From — ft. to — ft. From — ft. to — ft. From — ft. to — ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS: From GL-0 ft. to 3 ft. From 3 ft. to 5 ft. From — ft. to — ft. From — ft. to — ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL-0	1	CONCRETE & SAND			
1	3	CLAY SILT			
3	9	SILTY CLAY			
9	12	SANDY CLAY			
12	14	SILTY SAND			
14	16.5	SILTY CLAY			
		FLUSH MOUNT WATER			
		07-19-94-DONTAYLOR			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-15-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 09-06-94 under the business name of ERRETS DRILLING by (signature) <i>[Signature]</i>
--