

#2

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: HARVEY	SE 1/4 NW 1/4 SE 1/4	17	T 23 S	R 1E E

Distance and direction from nearest town or city street address of well if located within city?
301 N - MAIN - NEWTON

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #	Application Number:
LDYD T. SMITH 301 N+11TH ST. NEWTON KS 67119	
City, State, ZIP Code	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 9.8 ft. 2. - ft. 3. - ft. WELL'S STATIC WATER LEVEL 6.36 ft. below land surface measured on mo/day/yr 08-22-94 Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm Bore Hole Diameter 8.625 in. to 15 ft., and - in. to - ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes - No X ; If yes, mo/day/yr sample was submitted - Water Well Disinfected? Yes - No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued - Clamped -
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded -
2 PVC	7 Fiberglass		Threaded X
3 RMP (SR)			
4 ABS			
Blank casing diameter 2 in. to 4.8 ft., Dia - in. to - ft., Dia - in. to - ft.			
Casing height above land surface 0 in., weight SLX 40 lbs./ft. Wall thickness or gauge No. -			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify) -	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify) -	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 4.8 ft. to 14.8 ft., From - ft. to - ft.			
From 3.8 ft. to 15 ft., From - ft. to - ft.			
GRAVEL PACK INTERVALS: From - ft. to - ft., From - ft. to - ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other -
Grout Intervals: From 0 ft. to 1.8 ft., From 1.8 ft. to 3.8 ft., From - ft. to - ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				

Direction from well?	How many feet?				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
SLD 1	1	GRAVEL FILL			
1	2	CLAY SILT			
2	7	SILTY CLAY			
7	10	SANDY CLAY			
10	15	SANDY CLAY			
TD	15				
		FLUSH MOUNT WAIVER			
		07-19-94 - DAN TAYLOR			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-15-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 09-06-94 under the business name of EBBERTS DRILLING by (signature) Erberts
