

1 LOCATION OF WATER WELL: County: Harvey Fraction: N 1/4 SW 1/4 ME 1/4 Section Number: 26 Township Number: 23 Range Number: 1 E/W

Distance and direction from nearest town or city street address of well if located within city?
In City 226 Windward Dr.

2 WATER WELL OWNER: Gary Dunbaugh
RR#, St. Address, Box #: 226 Windward Dr.
City, State, ZIP Code: Newton, KS 67114

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 90 ft. ELEVATION: 10-21-94

Depth(s) Groundwater Encountered 1. 62 ft. 2. 12 ft. 3. 10-21-94 ft.

WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 10-21-94

Pump test data: Well water was 20 gpm ft. after 25 hours pumping 90 gpm

Est. Yield 20 gpm Well water was 25 ft. after 7 1/2 hours pumping 90 gpm

Bore Hole Diameter 9 in. to 25 ft. and 7 1/2 in. to 90 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded X Threaded X

Blank casing diameter 5 in. to 55 ft. Dia. 12 in. to 160 lbs./ft. Wall thickness or gauge No. 214

Casing height above land surface 12 in. weight CLASS 160

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 55 ft. to 90 ft. From 55 ft. to 90 ft. From 55 ft. to 90 ft.

GRAVEL PACK INTERVALS: From 55 ft. to 90 ft. From 55 ft. to 90 ft. From 55 ft. to 90 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 20 ft. From 20 ft. to 90 ft. From 90 ft. to 90 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? S How many feet? 40-50

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 12 Clay + Yellow Shale

12 62 Gray + Blue Shale

62 64 Crwm bled Shale + Water

64 90 Blue Shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-21-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 100 This Water Well Record was completed on (mo/day/yr) 10-26-94 under the business name of Backhus Drilling by (signature) Paul H. Backhus

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.