


1 LOCATION OF WATER WELL: County: Harvey Fraction: NW 1/4 SW 1/4 SW 1/4 Section Number: 22 Township Number: T 23 S Range Number: R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 1400 S. Spencer Rd

2 WATER WELL OWNER: Mid Continent Industries Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 1400 S. Spencer Rd Application Number:
City, State, ZIP Code: Newton KS 6744

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 17.5 ft. ELEVATION: 10.63 ft. below land surface measured on mo/day/yr 3-6-95
Depth(s) Groundwater Encountered 1. 11 ft. 2. 11 ft. 3. 11 ft.
WELL'S STATIC WATER LEVEL: 10.63 ft. below land surface measured on mo/day/yr 3-6-95
Pump test data: Well water was 8 gpm: Well water was 8 ft. after 8 hours pumping 8 gpm
Est. Yield 8 gpm: Well water was 8 ft. after 8 hours pumping 8 gpm
Bore Hole Diameter: 8 in. to 8 ft., and 8 in. to 8 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Flush Clamped Flush
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Flush Threaded Flush
7 Fiberglass
Blank casing diameter 2 in. to 2 ft., Dia. 2 in. to 2 ft., Dia. 2 in. to 2 ft.
Casing height above land surface Flush in., weight 7.03 lbs./ft. Wall thickness or gauge No. 154
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 7.5 ft. to 17.5 ft., From 7.5 ft. to 17.5 ft.
GRAVEL PACK INTERVALS: From 5.5 ft. to 17.5 ft., From 5.5 ft. to 17.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout intervals: From 5.5 ft. to 2 ft., From 5.5 ft. to 2 ft., From 5.5 ft. to 2 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? NE How many feet? 130

FROM		TO		LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	0.5	4.0	Asphalt			
0.5	4.0	4.0	5.0	Clay, Silty			
4.0	5.0	5.0	6.0	Clay, Sandy			
5.0	6.0	6.0	17.5	Clay, Sandy			
6.0	17.5	17.5		Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-6-95 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3-20-95
under the business name of BST by (signature) Alison Irwin