## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

Section number   Section number   Tourning numbe
Pistonce and direction from nearest town or city; Walface X. COO 3. Owner of well: Charles (City, states) (City
Sketch map:
Sketch map:
Sketch map:
Well depth AD ft.  7. Cobble toolRotaryDrivenDugHollow rodlettedBoredReverse rotary
Hollow rod   Jetted   Bored   Reverse rotory
8. Use:DomesticPublic supplyIndustryIrrigationAir conditioningStockLowOil field waterOther
Irrigation
Lawn Oil field water Other    SW   SE
9. Casing: Materialitelight: Above or below Threaded Welded Surface in. RMP PVC Weight ib ft. Diain. to ft. depth Wall Thickness: inches or Diain. to ft. depth Jagge No 10. Screen: Manufacturer's name
RMP PVC Weight Ibs./ft.  Dia. in. to ft. depth Wall Thickness: inches or  Dia. in. to ft. depth lage No.  10. Screen: Manufacturer's name  Type Dia.  Slot/gauze Length Set between ft. and ft.  Gravel pack? Size range of material  11. Static water level: mo./day/yr.  ft. below land surface Date 2 - 3 - 77  12. Pumping level below land surfaces:  15. ft. after hrs. pumping g.p.m.  ft. after ys. pumping g.p.m.  Estimated maximum yield Ogun 30 Mg. g.p.m.  Slot/gauze Length Ste between ft. and ft.  Gravel pack? Size range of material  11. Static water level: mo./day/yr.  12. Pumping level below land surface Date 2 - 3 - 77  12. Pumping level below land surfaces:  15. ft. after hrs. pumping g.p.m.  Estimated maximum yield Ogun 30 Mg. g.p.m.  Stimated maximum yield Ogun 30 Mg. g.p.m.  Yes No Date  14. Well head completion:  Pitless adapter Inches above grade  15. Well grouted?  With: Neat cement Bentonite Concrete  Death: From ft. to ft.
Type and color of material    From   To   Dia
Type and color of material  From To  Diain. toft. depth gage No  10. Screen: Manufacturer's name  Type Dia  Slot/gauze Length  Set betweenft. andft.  ft. andft.  ft. andft.  Gravel pack? Size range of material  11. Stgtic water level:mo./day/yr.  12. Pumping level below land surface Date77  12. Pumping level below land surfaces:
10. Screen: Manufacturer's name  Type
Slot/gauzeLength
Slot/gauzeLength
ft. andft. Gravel pack? Size range of material
Gravel pack? Size range of material    Size range of material   Size range of material   Size range of material   Size range of material   Size range of material
Sent of the selection   Sent of the sent
12. Pumping level below land surfaces: 15 ft. after hrs. pumping g.p.m
15 ft. after
Topsoil  Slice Shole  ft. afterhrs. pumpingg.p.m.  Estimated maximum yield
13. Water sample submitted: mo./day/yr.   Yes No _ Date
YesNoDate
Pitless adapter Inches above grade  2 8Pitless adapter Inches above grade  15. Well grouted? With: Neat cement Bentonite Concrete  Pepth: From ft. to ft.
Shire Shore  8 15. Well grouted? With: Neat cement Bentonite Concrete Pepth: From ft. to ft.
Chia Clay   8 /5   With: Neat cement Bentonite Concrete
7 UC Clau Depth: From ft. to ft.
Blue Shale 15 30 16. Nearest source of possible contamination:
Limistone 30 31 Well disinfected upon completion? Yes No
17.0
Blue Shale  31 100   Manufacturer's name Not installed   70   Manufacturer's name No model number HP Volts   70   Model number   70   Model
Length of drop pipe ft. capacity g.p.m.
Туре:
(Use a second sheet if needed) — Centrifugal — Other
Flavation: 19. Remarks: J J
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
pography:  2 - 3 - 77  is true to the best of my knowledge and belief.  Strands Budde 921
Hill Business name License No.
_ Slope Address
Upland