USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

						Topeka, Kansas 0002	20
Location of well:	nderson	Fraction NE 1/4	Sectio	n number	Twinship number	S R 20	@ ₩
Distance and discretion					ling M B		
Distance and direction	rom negrest fown or cit	EN OF Mildred	R.R. or street:			B. JEC	
eet address of well loca	tion if in city:				incaid, F	ans 666	139
Locate with "X" in sec	tion below:	Sketch	- II- la	, ,		in. Completion da	
N	TION BEIOW.	Head	BoreTion	1	Well depth 281		
! 📆	X	1) Hour -	STE NAK	(<u> </u>	7Cable tool	Rotary Driven	Dug
NW	NE	\sim	vallers of	with	Hollow rod	JettedBored	Reverse rotary
			Borettole Borettole 804 What Wallers	12	8. Use: Domestic		Industry
"	<u> </u>	Mu e 11	HT LET I	5		Air conditioning	Côtock Other
sw	SE			1	Lawn 9. Casing: Materi	ight: Abov	PE-1
	-)	13817	. 1	Threaded	Surface	12 in.
S	124.34		10	nche/	RMPPVC	Weight	Ibs./ft.
1 Mile -	-45		(0'3	APC		ft. depth Wall Thickne	ss; inches or
Type and color of mate	rial		From	19	10. Screen: Manufact	ft. depth gage No.	
		Soil		72	- Joseph Manoraci	Je7311	an
		<u> </u>	ellow 1	13	Туре	Dia	···
		Lime of	Jellow 3	اعترا	Slot/gauze 22	Length	80 "
		Shale-B	INE 12	1 11	Set between	ft. and	j:
all AMI W	TR	Chalky Lime - 1	vaite 107	141	Gravel pack?	Size range of material	2 To 3/4
•	•	8/2/4	R/40 141	147	11 Statie water level		no./day/yr.
	W		3700 274			and surface Date	116/18
		LIM	e that M.	148	12. Pumping level bel	ow land surfaces: hrs.pumping	g.p.m.
		>1214 8		167	ft. after	hrs. pumping	g.p.m.
			~ - 10 / 10 / 10 / 10 / 10 / 10 / 10 / 10	104	Estimated maximum yi		g.p.m.
)10/e=1	may 176	184	13. Water sample subm Yes		mo./day/yr.
		Thate Di	21/1502 184	194	14. Well head comple		
		~ · · · · · ·		1 3 15	Pitless adapter	Inches a	above grade
)halet.	hells 179	173	15. Well grouted?	MM S	1413
		Limit	Hond 215	245	With:Neat ceme	ent Bentor te	Concrete A DY
4) 4.11	~-	/	NA 245	772	Depth: From	II. TO	
HART W	<u> </u>	L/me.	104/ 27	21	ft. Direct	possible contamination on Type	5,7,c
		Shake	B/4 272	277	Well disinfected upon	completion?Y	es No
		Shake Lome	Hid 277	778	17. Pump:	Not insta	alled
2/0		Long	reia ZII	2 .0	Manufacturer's name Model number	HP	
TR 50m	e521T	Shale-Black	2- k 1278	1280	Length of drop pipe _	ft, capacity	g.p.m.
				7)	Type:		urbine
			280		Submersible Jet	-	eciprocating
(Use a second sheet if needed)					Centrifugal		Other
Elevation: 19.	Remarks:				20. Water well control		
ļ	**	of the second second				under my jurisdiction an	
oography:	in the second				Entella W	ny knowledge and belie Ell SerVice	296
Hill					Business name	No. T French	License No.
Slope					Addr & Constitution of the Addr & Constitution o	gall.	1
Upland					Signed	UNING	Day 10-16-8

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5