


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Linn</u>	<u>SW 1/4 SW 1/4 SE 1/4</u>	<u>11</u>	<u>T 23 S</u>	<u>R 24 E</u>

Distance and direction from nearest town or city street address of well if located within city?

13,800' West Southwest of Prescott

2 WATER WELL OWNER:	<u>Continental Coal</u>	Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box #	<u>4550 W. 109th St., Ste. 206</u>	
City, State, ZIP Code	<u>Leawood, KS. 66211</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>22</u> ft.	ELEVATION: <u>830</u> ft.
--	--	---------------------------

	Depth(s) Groundwater Encountered <u>1</u> ft. <u>None</u> ft. 2. ft. 3. ft.	
	WELL'S STATIC WATER LEVEL <u>N/A</u> ft. below land surface measured on mo/day/yr	
	Pump test data: Well water was <u>N/A</u> ft. after hours pumping gpm	
	Est. Yield gpm: Well water was ft. after hours pumping gpm	
	Bore Hole Diameter <u>5</u> in. to <u>22</u> ft., and in. to ft.	
WELL WATER TO BE USED AS:		
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well		
2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> 12 Other (Specify below)		
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted		
Water Well Disinfected? Yes No <u>X</u>		

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below)	Welded
<u>2 PVC</u> 4 ABS	7 Fiberglass	Threaded <u>1</u>
Blank casing diameter <u>2</u> in. to <u>22</u> ft. Dia. in. to ft. Dia. in. to ft.		
Casing height above land surface <u>36</u> in., weight <u>Schedule 40</u> lbs./ft. Wall thickness or gauge No.		

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	

SCREEN-PERFORATED INTERVALS:	From <u>12</u> ft. to <u>21</u> ft. From ft. to ft.
	From ft. to ft. From ft. to ft.
GRAVEL PACK INTERVALS:	From <u>10</u> ft. to <u>22</u> ft. From ft. to ft.
	From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From <u>8</u> ft. to <u>0</u> ft. From <u>10</u> ft. to <u>8</u> ft. From ft. to ft.	

What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Soil			
3	9	Clay			
9	11	Coal			
11	15	Shale			
15	22	Lime			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-28-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>545</u> This Water Well Record was completed on (mo/day/yr) <u>5-28-96</u> under the business name of <u>Glaze Drilling</u> by (signature) <u>Larry Towns for Calvin S. Glaze</u>	
---	--