


1 LOCATION OF WATER WELL: Fraction  $\frac{1}{4}$  NW  $\frac{1}{4}$  SE  $\frac{1}{4}$  Section Number 11 Township Number T 23 S Range Number R 24 E

Distance and direction from nearest town or city street address of well if located within city?  
11710' W SW Prescott

2 WATER WELL OWNER: Continental Coal  
RR#, St. Address, Box #: 4550 W. 109th St., Ste. 206  
City, State, ZIP Code: Leawood, KS. 66211  
Board of Agriculture, Division of Water Resource:  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 67 ft. ELEVATION: 869  
Depth(s) Groundwater Encountered 1. None ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL: N/A ft. below land surface measured on mo/day/yr  
Pump test data: Well water was N/A ft. after hours pumping gpm  
Est. Yield gpm: Well water was ft. after hours pumping gpm  
Bore Hole Diameter: 5 in. to 67 ft., and in. to ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter: 2 in. to 67 ft., Dia. In. to ft., Dia. In. to ft.  
Casing height above land surface: in., weight Schedule 40 lbs./ft. Wall thickness or gauge No.  
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 57 ft. to 67 ft., From ft. to ft.  
GRAVEL PACK INTERVALS: From 57 ft. to 67 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout intervals: From 51 ft. to 0 ft., From 51 ft. to 54 ft., From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage

Direction from well?		LITHOLOGIC LOG		How many feet?		PLUGGING INTERVALS
FROM	TO			FROM	TO	
0	1	Top soil				
1	4	Sub soil				
4	9	Dry sandy clay				
9	57	Blue shale				
57	59	Coal				
59	62	Under clay				
62	67	Limestone				

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-19-97 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 545 This Water Well Record was completed on (mo/day/yr)  
Under the business name of Glaze Drilling by (signature) Leaty Town for Glaze Drilling