

1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 NW 1/4 Section Number 17 Township Number T 23 S Range Number R 3 EW  
County: Butler  
Distance and direction from nearest town or city street address of well if located within city?

IN Elbing Ks.

2 WATER WELL OWNER: Elmo Murray  
RR#, St. Address, Box #: Box 42  
City, State, ZIP Code: Elbing Ks -  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
W  
E  
S  
4 DEPTH OF COMPLETED WELL: 76 ft. ELEVATION:  
Depth(s) Groundwater Encountered 1. 46 ft. 2. 60' ft. 3. ft.  
WELL'S STATIC WATER LEVEL: 34 ft. below land surface measured on mo/day/yr 5-21-83  
Pump test data: Well water was 60 ft. after 2 hours pumping 6/7 gpm  
Est. Yield 6 gpm: Well water was ft. after hours pumping gpm  
Bore Hole Diameter 11 in. to 76 ft., and in. to ft.  
WELL WATER TO BE USED AS:  
5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
Was a chemical/bacteriological sample submitted to Department? Yes X No: If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter 5 in. to 40 ft., Dia. in. to ft., Dia. in. to ft.  
Casing height above land surface 18 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 0.025 8 Saw cut factory 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft., From ft. to ft.  
From 60 ft. to 70 ft., From ft. to ft.  
GRAVEL PACK INTERVALS: From 10 ft. to 76 ft., From ft. to ft.  
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? EAST How many feet? 75'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	loam to br. clay			
5	10	yellow br. clay			
10	35	gray - brown - green clay			
35	40	red to gray shale			
40	70	gray to dark shale			
70		small fault			
70	76	gray - dark shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-21-83 (pump 8-30-83) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 175 This Water Well Record was completed on (mo/day/yr) 7-27-83 under the business name of Paul's Inc by (signature) Paul Brundhart

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.