WATER WELL RECORD			Form W	WC-5	Division	n of Water Resources App.	No	
Cou	CATION OF WA		Fraction 1/4)		$\Box OJ$	umber Township No.	ROLXE □W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						sitioning System (GPS)		
	nom made of the of measurement is detected, enough the services of the service					Latitude: (in decimal degrees) Longitude: (in decimal degrees)		
			0 . 1		Elevation:	: WGS 84,		
2 W	TER WELL OV	VNER: HW	150191	3,	Collection	Method:		
RR#, Street Address, Box #: 101 (w 15 (407) Bloom City, State, ZIP Code: 101					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Huberingson, XI 67502 Est. Accuracy: [] <3 m, [] 3-5 m, [] 5-15 m, [] >15 m								
	CATE WELL TH AN "X" IN	4 DEPTH OF C	COMPLETED WEL	ı32		ft.		
SEC	TION BOX:	Depth(s) Ground	water Encountered	(I) ₂	ft.	(2) ft.	(3)	
<u> </u>	SECTION BOX: N Depth(s) Groundwater Encountered (1)							
N	W NE	EST. YIELD	gpm Well wate	er was	ft. afte	r hours put	mping gpm	
w	W E Bore Hole Diameterin. toft., andin. toft.						ft.	
-	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below							
18	☐ Irrigation ☐ Industrial ★ Domestic-lawn & garden ☐ Monitoring well							
<u> </u>	Was a chemical/bacteriological sample submitted to Department? Yes X No							
S If yes, mo/day/yr sample was submitted								
5 TYPE OF CASING USED: Steel X PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in to ft., Diameter ft., Diameter ft., Diameter ft. Casing height above land surface in in, Weight 2.2 in lbs./ft., Wall thickness or gauge No. 1.5 in to ft.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From								
From ft. to ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 1.3 ft. to 32 ft., From ft. to ft. From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
Dire	ction from well	The Co			from well			
FROM	TO	LITHOLOG	CLOG	FROM	TO LI	THO, LOG (cont.) or PL	UGGING INTERVALS	
<u>Q</u>	13/0		ja; l	-				
12	7 0	41-5:18	accordio	Hack				
18	32 Dea	sile or	1160					
	4.							
	+							
				-				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No								
inder the business name of State of Sta								
INSTRUCTIONS: Ilee typerriter or hall point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
Celephor	white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Felephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
nttp://ww	http://www.kdheks.gov/waterwell/index.html.							
NA MIG 1919								