

MW-3 2311026

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		SW 1/4 SW 1/4 SW 1/4	33	T 24 S	R 1 Q/W
Distance and direction from nearest town or city street address of well if located within city? 201 S. 56th Ave, KS SW 125th Street North AND Old Highway 81 North					
2 WATER WELL OWNER: KDHE					
RR#, St. Address, Box #: FORBES FIELD BUILDING 740				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: TOPEKA, KS 66620				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 19.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 17.76 ft. below land surface measured on mo/day/yr 8-11-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	7 Fiberglass		Welded Threaded FLUSH
Blank casing diameter 2 in. to ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface FLUSH in. weight 703 lbs./ft. Wall thickness or gauge No. 154					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 15.5 ft. to 25.5 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 13.5 ft. to 25.5 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 13.5 ft. to 1.5 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? NORTH		How many feet? 80 AND 130			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	CLAY, SILTY, SAND			
1.0	3.0	CLAY, V. SILTY, SAND			
3.0	12.5	CLAY, SILTY, SOME SAND			
12.5	17.5	CLAY, SILTY, WITH SAND			
17.5	25.5	SAND, SILTY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-11-95 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 531		This Water Well Record was completed on (mo/day/yr) 8-17-95			
under the business name of GSI		by (signature) Steve Nardella			